



MODEL:

PPC-51xxA-H61

**Industrial Panel PC for 2nd/3rd Generation Intel® Core™,
Pentium® or Celeron® CPU, Intel® H61 Express Chipset,
Touchscreen, USB 3.0, Dual Gigabit LAN supporting SFP Fiber,
IP 66 Compliant Front Panel and RoHS Compliant**

User Manual

Rev. 1.03 – March 25, 2015



Revision

Date	Version	Changes
March 25, 2015	1.03	Modified Section 1.7: Specifications Added Appendix A: Regulatory Compliance
January 20, 2015	1.02	Changed IP 65 to IP 66
June 28, 2013	1.01	Updated Figure 3-25: PPC-5150A-H61 Panel Cutout Dimensions Added the limitation of the expansion card dimensions
October 26, 2012	1.00	Initial release

Copyright

COPYRIGHT NOTICE

The information in this document is subject to change without prior notice in order to improve reliability, design and function and does not represent a commitment on the part of the manufacturer.

In no event will the manufacturer be liable for direct, indirect, special, incidental, or consequential damages arising out of the use or inability to use the product or documentation, even if advised of the possibility of such damages.

This document contains proprietary information protected by copyright. All rights are reserved. No part of this manual may be reproduced by any mechanical, electronic, or other means in any form without prior written permission of the manufacturer.

TRADEMARKS

All registered trademarks and product names mentioned herein are used for identification purposes only and may be trademarks and/or registered trademarks of their respective owners.

Table of Contents

1 INTRODUCTION.....	1
1.1 OVERVIEW.....	2
1.2 MODEL VARIATIONS	2
1.3 FEATURES.....	3
1.4 EXTERNAL OVERVIEW.....	4
<i>1.4.1 Front Panel</i>	<i>4</i>
<i>1.4.2 Rear Panel</i>	<i>5</i>
<i>1.4.3 Top Panel</i>	<i>5</i>
<i>1.4.4 Bottom Panel.....</i>	<i>6</i>
<i>1.4.5 Left Panel.....</i>	<i>9</i>
<i>1.4.6 Right Panel.....</i>	<i>9</i>
1.5 INTERNAL OVERVIEW.....	10
1.6 DIMENSIONS.....	11
<i>1.6.1 PPC-5150A-H61 Dimensions</i>	<i>11</i>
<i>1.6.2 PPC-5170A-H61 Dimensions</i>	<i>12</i>
<i>1.6.3 PPC-5190A-H61 Dimensions</i>	<i>13</i>
1.7 SPECIFICATIONS	14
2 UNPACKING	17
2.1 UNPACKING	18
2.2 PACKING LIST.....	19
2.3 OPTIONAL ITEMS	20
3 INSTALLATION	22
3.1 ANTI-STATIC PRECAUTIONS	23
3.2 INSTALLATION PRECAUTIONS	23
3.3 PREINSTALLED COMPONENTS.....	24
3.4 INSTALLATION AND CONFIGURATION STEPS	24
3.5 REMOVING THE BACK COVER	25
3.6 JUMPER SETTINGS	26
<i>3.6.1 Access the Jumpers</i>	<i>26</i>

PPC-51xxA-H61 Panel PC

3.6.2 Preconfigured Jumpers	27
3.6.3 COM1 to COM5 Pin 9 Setting Jumpers	27
3.6.4 COM5 RS-232/422/485 Serial Port Selection Jumper	29
3.7 DRIVE INSTALLATION	30
3.7.1 Hard Drive Installation.....	30
3.7.2 CompactFlash® Card Installation	32
3.7.3 Optical Disk Drive Installation (Optional).....	33
3.8 PCI EXPANSION CARD INSTALLATION (OPTIONAL)	37
3.9 PCIE EXPANSION CARD INSTALLATION (OPTIONAL)	40
3.10 AT/ATX MODE SELECTION	42
3.11 MOUNTING THE SYSTEM	43
3.11.1 Wall Mounting	43
3.11.2 Panel Mounting.....	46
3.11.3 Rack and Cabinet Installation.....	49
3.11.4 Arm Mounting	49
3.11.5 Stand Mounting	50
3.12 SFP FIBER MODULE INSTALLATION (OPTIONAL).....	51
3.13 BOTTOM PANEL CONNECTORS.....	52
3.13.1 Audio Connectors.....	52
3.13.2 RJ-45 LAN Connectors	53
3.13.3 RS-232 Serial Ports (COM1, COM2, COM3, COM4)	54
3.13.4 RS-232/422/485 Serial Port (COM5)	56
3.13.5 SFP Fiber LAN Connectors	57
3.13.6 USB 2.0 Connectors.....	57
3.13.7 USB 3.0 Connectors.....	58
3.13.8 VGA Connector	59
3.14 DRIVER INSTALLATION	60
4 SYSTEM MAINTENANCE	62
4.1 SYSTEM MAINTENANCE INTRODUCTION	63
4.2 MOTHERBOARD REPLACEMENT	63
4.3 BACK COVER REMOVAL.....	63
4.4 SO-DIMM REPLACEMENT.....	64
4.5 ELEVATED PLATFORM REMOVAL	65
4.6 PSU MODULE REPLACEMENT	67

<i>4.6.1 Remove the Old PSU</i>	67
<i>4.6.2 Install the New PSU</i>	68
4.7 SYSTEM COOLING FAN REPLACEMENT	69
<i>4.7.1 Remove the Old System Cooling Fans</i>	69
<i>4.7.2 Install the New System Cooling Fans</i>	70
5 BIOS SETUP	71
<i>5.1 INTRODUCTION</i>	72
<i>5.1.1 Starting Setup</i>	72
<i>5.1.2 Using Setup</i>	72
<i>5.1.3 Getting Help</i>	73
<i>5.1.4 Unable to Reboot after Configuration Changes</i>	73
<i>5.1.5 BIOS Menu Bar</i>	73
<i>5.2 MAIN</i>	74
<i>5.3 ADVANCED</i>	75
<i>5.3.1 ACPI Settings</i>	76
<i>5.3.2 RTC Wake Settings</i>	77
<i>5.3.3 CPU Configuration</i>	78
<i>5.3.4 SATA Configuration</i>	80
<i>5.3.5 USB Configuration</i>	81
<i>5.3.6 F81866 Super IO Configuration</i>	82
<i>5.3.6.1 Serial Port n Configuration</i>	83
<i>5.3.7 F81866 H/W Monitor</i>	88
<i>5.3.7.1 Smart Fan Mode Configuration</i>	88
<i>5.3.8 Serial Port Console Redirection</i>	90
<i>5.3.8.1 Console Redirection Settings</i>	91
<i>5.4 CHIPSET</i>	93
<i>5.4.1 PCH-IO Configuration</i>	94
<i>5.4.1.1 PCH Azalia Configuration</i>	95
<i>5.4.2 System Agent (SA) Configuration</i>	96
<i>5.4.2.1 Graphics Configuration</i>	96
<i>5.4.2.2 Memory Configuration</i>	99
<i>5.5 BOOT</i>	99
<i>5.6 SECURITY</i>	101
<i>5.7 SAVE & EXIT</i>	102

6 INTERFACE CONNECTORS	104
6.1 PERIPHERAL INTERFACE CONNECTORS.....	105
6.2 INTERNAL PERIPHERAL CONNECTORS	106
6.2.1 +12V Power Source Connector (CPU12V1)	108
6.2.2 ATX Power Connector (ATX1).....	108
6.2.3 CompactFlash® Card Slot (CF1).....	109
6.2.4 DIO Connector (DIO1).....	110
6.2.5 Fan Connector (CPU_FAN1/SYS_FAN1/SYS_FAN2/SYS_FAN3)	110
6.2.6 I2C Connector (I2C_1).....	110
6.2.7 Internal Audio Connector (SPKLI)	111
6.2.8 Internal Audio Connector (SPKR1).....	111
6.2.9 Internal Power Button Connector (PWR_SW1)	111
6.2.10 Internal Power Button Connector (PWR_SW2)	111
6.2.11 K Type Thermocouple Connectors (K_TYPE1/K_TYPE2).....	112
6.2.12 LVDS Backlight Connector (INVERTER1).....	112
6.2.13 LVDS Connector (LVDS1)	112
6.2.14 PCIe Mini Card Slot (MINI_PCIE1)	113
6.2.15 SATA 3Gb/s Connectors (SATA1/SATA2).....	114
6.2.16 SATA Power Connectors (JSATA_PWR1/JSATA_PWR2).....	114
6.2.17 SFP Fiber LED Connector (F_LED1).....	115
6.2.18 SMBus Connector (SMBUS_1).....	115
6.2.19 SPI Flash Connector (JSPII).....	115
6.2.20 Touch Panel Connector (TOUCH1).....	116
6.2.21 USB 2.0 Connectors (USB1/USB2/USB3/USB4)	116
6.3 EXTERNAL INTERFACE PANEL CONNECTORS	116
6.3.1 RJ-45 LAN Connector (LAN1/2).....	117
6.3.2 RS-232 Serial Ports (COM1/2, COM3/4).....	117
6.3.3 RS-232/422/485 Serial Port (COM5)	118
6.3.4 USB 2.0 Connectors (USB_CON2).....	118
6.3.5 USB 3.0 Connectors (USB_CON1).....	118
6.3.6 VGA Connector (VGA1).....	119
6.4 PRECONFIGURED JUMPER SETTINGS.....	119
6.4.1 CF Card Power Selection Jumper (JP1)	120
6.4.2 CPU Fan Type Selection Jumper (JCPUFAN1).....	120

<i>6.4.3 Inverter Brightness Voltage Selection Jumper (J_ADJ1)</i>	120
<i>6.4.4 LCD Power Selection Jumper (JLCD_PWR1)</i>	121
<i>6.4.5 Panel Type and Resolution Selection Jumper (JLCD_SET1)</i>	121
<i>6.4.6 Pull High/Low Selection (for RS-422/485 only) Jumper (UART_SEL1)</i>	121
<i>6.4.7 System Fan Type Selection Jumper (JSYSFAN1/JSYSFAN3)</i>	122
<i>6.4.8 Touchscreen Selection Jumper (JTOUCH1)</i>	122
<i>6.4.9 USB1~USB4 Power Selection Jumpers</i>	122
A REGULATORY COMPLIANCE	123
B BIOS CONFIGURATION OPTIONS	128
B.1 BIOS CONFIGURATION OPTIONS	129
C SAFETY PRECAUTIONS	131
C.1 SAFETY PRECAUTIONS	132
<i>C.1.1 General Safety Precautions</i>	132
<i>C.1.2 Anti-static Precautions</i>	133
<i>C.1.3 Product Disposal</i>	133
C.2 MAINTENANCE AND CLEANING PRECAUTIONS	134
<i>C.2.1 Maintenance and Cleaning</i>	134
<i>C.2.2 Cleaning Tools</i>	135
D WATCHDOG TIMER	136
E HAZARDOUS MATERIALS DISCLOSURE	139
E.1 HAZARDOUS MATERIAL DISCLOSURE TABLE FOR IPB PRODUCTS CERTIFIED AS ROHS COMPLIANT UNDER 2002/95/EC WITHOUT MERCURY	140

List of Figures

Figure 1-1: PPC-51xxA-H61 Panel PC.....	2
Figure 1-2: Front View	4
Figure 1-3: Rear View	5
Figure 1-4: Top View.....	5
Figure 1-5: PPC-5150A-H61/PPC-5170A-H61 Bottom View	7
Figure 1-6: PPC-5190A-H61 Bottom View	8
Figure 1-7: Left View.....	9
Figure 1-8: Right View	9
Figure 1-9: Internal Components	10
Figure 1-10: PPC-5150A-H61 Dimensions (mm).....	11
Figure 1-11: PPC-5170A-H61 Dimensions (mm).....	12
Figure 1-12: PPC-5190A-H61 Dimensions (mm).....	13
Figure 3-1: PPC-5150A-H61 Back Cover Retention Screws.....	25
Figure 3-2: COM1 to COM5 Pin 9 Setting Jumper Locations	28
Figure 3-3: COM5 RS-232/422/485 Serial Port Selection Jumper Location	29
Figure 3-4: HDD Bracket Retention Screws.....	30
Figure 3-5: HDD Retention Screws	31
Figure 3-6: Replacing the HDD Bracket	31
Figure 3-7: CompactFlash® Cover Plate	32
Figure 3-8: Installing the CompactFlash® Card	32
Figure 3-9: Replacing the CompactFlash® Cover Plate	33
Figure 3-10: Optical Drive Bracket Retention Screws	34
Figure 3-11: Optical Drive Blank Plate Assembly	34
Figure 3-12: Optical Drive Screws	35
Figure 3-13: Optical Drive SATA Cable	35
Figure 3-14: Replacing the Optical Drive Bracket.....	36
Figure 3-15: Installing the PCI Riser Card.....	38
Figure 3-16: Expansion Slot Retention Screw	38
Figure 3-17: Installing the PCI Card.....	39
Figure 3-18: Installing the PCIe Riser Card.....	41
Figure 3-19: Expansion Slot Retention Screw	41

Figure 3-20: Installing the PCIe Card.....	42
Figure 3-21: AT/ATX Mode Selection.....	42
Figure 3-22: Wall-mounting Bracket	44
Figure 3-23: Mount the Chassis	45
Figure 3-24: Secure the Chassis	46
Figure 3-25: PPC-5150A-H61 Panel Cutout Dimensions	47
Figure 3-26: PPC-5170A-H61 Panel Cutout Dimensions	47
Figure 3-27: PPC-5190A-H61 Panel Cutout Dimensions	47
Figure 3-28: Panel Mounting Clamp Positions	48
Figure 3-29: Tighten the Panel Mounting Clamp Screws	49
Figure 3-30: Arm Mounting Retention Screw Holes.....	50
Figure 3-31: Stand Mounting Retention Screw Holes.....	51
Figure 3-32: SFP Fiber Module Installation.....	52
Figure 3-33: RJ-45 LAN Connector	53
Figure 3-34: LAN Connection	54
Figure 3-35: RS-232 Serial Port	54
Figure 3-36: RS-232 Serial Device Connector	55
Figure 3-37: RS-232/422/485 Serial Port.....	56
Figure 3-38: RS-232/422/485 Serial Device Connector	57
Figure 3-39: USB Device Connection	58
Figure 3-40: VGA Connector	59
Figure 3-41: VGA Connector	60
Figure 3-42: Driver Menu	61
Figure 4-1: SO-DIMM Module Locations.....	64
Figure 4-2: SO-DIMM Module Installation.....	65
Figure 4-3: PPC-5150A-H61 Top Panel Elevated Platform Screws.....	65
Figure 4-4: PPC-5150A-H61Side Panel Elevated Platform Screws.....	66
Figure 4-5: PPC-5150A-H61Bottom Panel Elevated Platform Screws.....	66
Figure 4-6: PPC-5150A-H61Internal Elevated Platform Screws	66
Figure 4-7: PSU Power Cables	67
Figure 4-8: PSU Bottom Panel Retention Screws	68
Figure 4-9: PSU Bottom Panel Screws	68
Figure 4-10: System Cooling Fans Motherboard Connector	69
Figure 4-11: System Cooling Fans Left Panel Retention Screws	70
Figure 6-1: Main Board Layout Diagram (Front Side)	105

Figure 6-2: Main Board Layout Diagram (Solder Side) 106

List of Tables

Table 1-1: Model Variations	3
Table 1-2: System Specifications.....	16
Table 2-1: Packing List.....	19
Table 2-2: Optional Items.....	21
Table 3-1: Jumpers	26
Table 3-2: Preconfigured Jumpers	27
Table 3-3: COM1 to COM5 Pin 9 Setting Jumper Settings	28
Table 3-4: COM5 RS-232/422/485 Serial Port Selection Jumper Settings.....	29
Table 3-5: LAN Pinouts	53
Table 3-6: RJ-45 LAN Connector LEDs	53
Table 3-7: RS-232 Serial Port Pinouts	55
Table 3-8: RS-232/422/485 Serial Port Pinouts	56
Table 3-9: USB 2.0 Port Pinouts	57
Table 3-10: USB 3.0 Port Pinouts.....	59
Table 3-11: VGA Connector Pinouts.....	59
Table 5-1: BIOS Navigation Keys	73
Table 6-1: Peripheral Interface Connectors	108
Table 6-2: +12V Power Source Connector (CPU12V1) Pinouts	108
Table 6-3: ATX Power Connector (ATX1) Pinouts.....	108
Table 6-4: CompactFlash® Card Slot (CF1) Pinouts.....	109
Table 6-5: DIO Connector (DIO1) Pinouts	110
Table 6-6: Fan Connector Pinouts	110
Table 6-7: Fan Connector (I2C_1) Pinouts	110
Table 6-8: Internal Audio Connector (SPKL1) Pinouts	111
Table 6-9: Internal Audio Connector (SPKR1) Pinouts.....	111
Table 6-10: Internal Power Button Connector (PWR_SW1) Pinouts	111
Table 6-11: Internal Power Button Connector (PWR_SW2) Pinouts	111
Table 6-12: K Type Thermocouple Connectors (K_TYPE1/K_TYPE2) Pinouts	112
Table 6-13: LVDS Backlight Connector (INVERTER1) Pinouts	112
Table 6-14: LVDS Connector (LVDS1) Pinouts.....	113
Table 6-15: PCIe Mini Card Slot (MINI_PCIE1) Pinouts.....	114

PPC-51xxA-H61 Panel PC

Table 6-16: SATA 3Gb/s Connectors (SATA1/SATA2) Pinouts	114
Table 6-17: SATA Power Connectors (JSATA_PWR1/JSATA_PWR2 Pinouts	114
Table 6-18: SATA Power Connectors (JSATA_PWR1/JSATA_PWR2 Pinouts	115
Table 6-19: SMBus Connector (SMBUS_1) Pinouts.....	115
Table 6-20: SPI Flash Connector (JSPI1) Pinouts.....	115
Table 6-21: Touch Panel Connector (TOUCH1) Pinouts.....	116
Table 6-22: USB 2.0 Connector (USB1/USB2/USB3/USB4) Pinouts.....	116
Table 6-23: Rear Panel Connectors	117
Table 6-24: RJ-45 LAN Connector Pinouts	117
Table 6-25: RS-232 Serial Port Pinouts	117
Table 6-26: RS-232/422/485 Serial Port Pinouts	118
Table 6-27: USB 2.0 Connectors (USB_CON2) Pinouts.....	118
Table 6-28: USB 3.0 Connectors (USB_CON1) Pinouts.....	119
Table 6-29: VGA Connector (VGA1) Pinouts	119
Table 6-30: Preconfigured Jumpers	120
Table 6-31: CF Card Power Selection Jumper (JP1) Settings.....	120
Table 6-32: CPU Fan Type Selection Jumper (JCPUFAN1) Settings	120
Table 6-33: Inverter Brightness Voltage Selection Jumper (J_ADJ1) Settings	120
Table 6-34: LCD Power Selection Jumper (JLCD_PWR1) Settings.....	121
Table 6-35: Panel Type and Resolution Selection Jumper (JLCD_SET1) Settings	121
Table 6-36: Pull High/Low Selection (for RS-422/485 only) Jumper (UART_SEL1) Settings..	121
Table 6-37: System Fan Type Selection Jumper Settings.....	122
Table 6-38: Touchscreen Selection Jumper (JTOUCH1) Settings.....	122
Table 6-39: USB1~USB4 Power Selection Jumpers Settings	122

Chapter

1

Introduction

1.1 Overview



Figure 1-1: PPC-51xxA-H61 Panel PC

The PPC-51xxA-H61 panel PC is for industrial environments like production lines and machine automation. The PPC-51xxA-H61 provides all the features of a PC, combined with a touch panel screen for mouse and keyboard free data input. The PPC-51xxA-H61 provides wired networking for integration into company networks. The major external device connections include USB 2.0, USB 3.0 and serial port connectors. Storage options include a 2.5" hard drive, a CompactFlash® card slot and optional mSATA, allowing for flexibility in choosing solid state drives or traditional hard drives. A VGA output on the bottom panel allows the PPC-51xxA-H61 to connect to a second screen for duplicating the screen contents or extending the user interface.

1.2 Model Variations

The model numbers and model variations are listed below.

Model	CPU	Power	Screen
PPC-5150A-H61-P/R-R10	Intel® Pentium® G6xxT Dual Core (above 2.2 GHz)	AC input	15"
PPC-5150AD-H61-P/R-R10		18~36 V DC input	15"
PPC-5150A-H61-i3/R-R10	Intel® Core™ i3 2xxxT Dual Core (above 2.5 GHz)	AC input	15"
PPC-5150AD-H61-i3/R-R10		18~36 V DC input	15"

PPC-51xxA-H61 Panel PC

Model	CPU	Power	Screen
PPC-5150A-H61-i5/R-R10	Intel® Core™ i5 2xxxT Dual Core (above 2.7 GHz)	AC input	15"
PPC-5150AD-H61-i5/R-R10		18~36 V DC input	15"
PPC-5170A-H61-P/R-R10	Intel® Pentium® G6xxT Dual Core (above 2.2 GHz)	AC input	17"
PPC-5170AD-H61-P/R-R10		18~36 V DC input	17"
PPC-5170A-H61-i3/R-R10	Intel® Core™ i3 2xxxT Dual Core (above 2.5 GHz)	AC input	17"
PPC-5170AD-H61-i3/R-R10		18~36 V DC input	17"
PPC-5170A-H61-i5/R-R10	Intel® Core™ i5 2xxxT Dual Core (above 2.7 GHz)	AC input	17"
PPC-5170AD-H61-i5/R-R10		18~36 V DC input	17"
PPC-5190A-H61-P/R-R10	Intel® Pentium® G6xxT Dual Core (above 2.2 GHz)	AC input	19"
PPC-5190AD-H61-P/R-R10		18~36 V DC input	19"
PPC-5190A-H61-i3/R-R10	Intel® Core™ i3 2xxxT Dual Core (above 2.5 GHz)	AC input	19"
PPC-5190AD-H61-i3/R-R10		18~36 V DC input	19"
PPC-5190A-H61-i5/R-R10	Intel® Core™ i5 2xxxT Dual Core (above 2.7 GHz)	AC input	19"
PPC-5190AD-H61-i5/R-R10		18~36 V DC input	19"

Table 1-1: Model Variations

1.3 Features

Some of the features of the PPC-51xxA-H61 panel PC include:

- Mainstream panel PC design with dual display function.
- Aluminum die-casting front panel meet IP 66 water proof standard
- High brightness TFT LCD panel with LED backlight
- Supports 2nd/3rd generation Intel® Core™, Pentium® and Celeron® processors
- Intel® H61 Express Chipset
- Dual DDR3 SO-DIMM (system max. 16 GB)
- Multiple storage options: 2.5" SATA HDD, CompactFlash® card and mSATA
- Dual Gigabit LAN supporting either RJ-45 or SFP fiber
- Optional PCIe Mini 802.11b/g/n wireless module

- Optional PCI/PCIe x1 expansion slot
- Supports slim type optical disk drive
- Includes the following I/O ports:
 - Five COM ports (one RS-232/422/485)
 - One CompactFlash® slot
 - One VGA port
 - RJ-45 and SFP fiber Gigabit LAN ports
 - USB 3.0 ports
 - USB 2.0 ports
- RoHS compliant

1.4 External Overview

The PPC-51xxA-H61 panel PC is comprised of an LCD screen, aluminum front panel and heavy duty steel rear and side panels. The rear panel provides screw holes for wall and an arm mounting. The right panel provides access to a slim type optical disk drive bay. The bottom panel provides access to external interface connectors that include GbE, USB 3.0, USB 2.0, audio, serial port connectors, VGA port and a CompactFlash® card slot.

1.4.1 Front Panel

The front panel of the PPC-51xxA-H61 (**Figure 1-2**) is a flat panel TFT LCD screen surrounded by an aluminum frame.




Figure 1-2: Front View

PPC-51xxA-H61 Panel PC

1.4.2 Rear Panel

The rear panel has a fan vent, four VESA standard mounting holes and several retention screw holes. The VESA mounting holes are circled in **Figure 1-3**.



Figure 1-3: Rear View

1.4.3 Top Panel

The top panel has panel mounting clamp slots, a fan vent and retention screws for securing the drive bay bracket. The numbers and locations of the panel mounting clamp slots may vary by models.




Figure 1-4: Top View

1.4.4 Bottom Panel

The bottom panel has the following interfaces:

- 1 x Power input connector
- 1 x Power switch
- 2 x USB 3.0 connectors
- 4 x USB 2.0 connectors (six USB 2.0 ports for PPC-5190A-H61)
- 1 x Reset button
- 1 x Clear CMOS button
- 2 x RJ-45 GbE connectors
- 2 x SFP fiber Gigabit LAN connectors
- 4 x RS-232 connectors (COM1, COM2, COM3 and COM4)
- 1 x RS-232/422/485 connector (COM5)
- 1 x PCI/PCIe x1 expansion card slot
- 1 x Line-out jack
- 1 x Mic-in jack
- 1 x VGA connector
- 1 x CompactFlash® card slot
- 1 x AT/ATX switch
- 2 x SFP fiber indicators

PPC-51xxA-H61 Panel PC




Figure 1-5: PPC-5150A-H61/PPC-5170A-H61 Bottom View




Figure 1-6: PPC-5190A-H61 Bottom View

**NOTE:**

The PPC-5190A-H61 provides two types of Gigabit LAN, one is SFP fiber and the other is RJ-45. The user can use either one of it. When a SFP fiber LAN port is linked, the corresponding SFP fiber indicator lights up.

PPC-51xxA-H61 Panel PC

1.4.5 Left Panel

The left panel has two cooling fans that cool the interior of the system and slots for installing the panel mounting clamps. The numbers and locations of the panel mounting clamp slots may vary by models.




Figure 1-7: Left View

1.4.6 Right Panel

The right panel has a slim type optical disk drive bay for ODD installation and slots for installing the panel mounting clamps. The numbers and locations of the panel mounting clamp slots may vary by models.




Figure 1-8: Right View

1.5 Internal Overview

The PPC-51xxA-H61 internal components are configured in three levels. The PSU cover bracket to the left (**Figure 1-9**) supports the hard drive and optical drive brackets. Below the PSU cover bracket is the power supply. On the same level as the power supply is the motherboard. Below the motherboard and PSU level is an LCD panel. An overview picture of the internal components is shown in **Figure 1-9** below.




Figure 1-9: Internal Components

PPC-51xxA-H61 Panel PC

1.6 Dimensions

1.6.1 PPC-5150A-H61 Dimensions




Figure 1-10: PPC-5150A-H61 Dimensions (mm)

1.6.2 PPC-5170A-H61 Dimensions




Figure 1-11: PPC-5170A-H61 Dimensions (mm)

PPC-51xxA-H61 Panel PC

1.6.3 PPC-5190A-H61 Dimensions




Figure 1-12: PPC-5190A-H61 Dimensions (mm)

1.7 Specifications

The technical specifications for the PPC-51xxA-H61 system are listed in **Table 1-2**.

	PPC-5150A-H61	PPC-5170A-H61	PPC-5190A-H61
LCD Size	15"	17"	19"
Max. Resolution	1024 (W) x 768 (H)	1280 (W) x 1024 (H)	1280 (W) x 1024 (H)
Brightness	400 cd/m ²	350 cd/m ²	350 cd/m ²
Contrast Ratio	700:1	800:1	1000:1
Pixel Pitch (mm)	0.297 x 0.297	0.264 x 0.264	0.294 x 0.294
Viewing Angle (V-H)	140/160	170/160	160/170
LCD Color	16.2M	16.7M	16.7M
Backlight MTBF	50,000 hours	50,000 hours	50,000 hours
SBC Model	POS-H61		
CPU	2nd/3rd generation Intel® Core™, Pentium® or Celeron® CPU		
Express Chipset	Intel® H61		
Memory	Two 204-pin DDR3 SO-DIMM slots (system max. 16 GB)		
Solid State Drive (SSD)	CompactFlash® Type II and mSATA (optional)		
Drive Bays	One 2.5" SATA HDD bay with anti-shock		
	One slim type optical disk drive bay		
Expansion Slots	One PCIe Mini		
	Optional riser card:		
	One PCI or One PCIe x4 with PCIe x1 signal		
Touchscreen	5-wire resistive type with RS-232 interface		
Wireless LAN	IEEE 802.11b/g/n 2T2R mode WLAN via internal PCIe Mini card (optional)		

PPC-51xxA-H61 Panel PC

	PPC-5150A-H61	PPC-5170A-H61	PPC-5190A-H61
I/O Ports, Switches and Indicators	2 x USB 3.0 4 x USB 2.0 (six USB 2.0 ports for PPC-5190A-H61 series) 4 x RS-232 (COM1 ~ COM4) 1 x RS-232/422/485 (COM5) 1 x VGA connector 2 x RJ-45 LAN connectors 2 x SFP fiber LAN connectors 2 x Audio jacks (Line-out and Mic-in) 1 x CMOS reset button 1 x AT/ATX switch 1 x Power switch 2 x SFP fiber LAN indicators		
Mounting	VESA 100 mm x 100 mm (panel, wall, rack, stand and arm)		
Chassis Construction	Heavy-duty steel		
Front Panel Construction	Aluminum		
Vibration	5 Hz ~ 17 Hz 0.1" double amplitude displacement 17 Hz ~ 640 Hz 1.5G acceleration peak to peak		
Shock	10G acceleration part to part (11 ms)		
Humidity	10% ~ 95%, non-condensing		
Operating Temperature (Ambient with air flow)	-20°C ~ 60°C	-20°C ~ 60°C	-10°C ~ 50°C
Storage Temperature	-30°C ~ 70°C	-30°C ~ 70°C	-20°C ~ 60°C
Net/Gross Weight	7 kg/11 kg	8 kg/12 kg	12.6 kg/18.2 kg
Dimensions (W x H x D) (mm)	410 x 309 x 110.5	452 x 356 x 115	482 x 399 x 115

	PPC-5150A-H61	PPC-5170A-H61	PPC-5190A-H61
AC Input ATX (A Model)	ACE-A622A-RS <ul style="list-style-type: none">▪ 220 W▪ Input: 90 V AC~264 V AC, 50/60 Hz▪ Output (max.): 3.3 A@14 A, 5 V@16 A, 12 V@10 A, -12 V@0.8 A		
DC Input ATX (AD Model)	ACE-4520C-RS <ul style="list-style-type: none">▪ 200 W▪ Input: 24 V DC (18~36 V DC), 50/60 Hz▪ -Output (max.): 3.3 A@12 A, 5 V@12 A, 12 V@15.4 A, -12 V@0.5 A		

Table 1-2: System Specifications

Chapter

2

Unpacking

2.1 Unpacking

To unpack the panel PC, follow the steps below:



WARNING!

The front side LCD screen has a protective plastic cover stuck to the screen. Only remove the plastic cover after the panel PC has been properly installed. This ensures the screen is protected during the installation process.

-
- Step 1:** Use box cutters, a knife or a sharp pair of scissors that seals the top side of the external (second) box.
 - Step 2:** Open the external (second) box.
 - Step 3:** Use box cutters, a knife or a sharp pair of scissors that seals the top side of the internal (first) box.
 - Step 4:** Lift the monitor out of the boxes.
 - Step 5:** Remove both polystyrene ends, one from each side.
 - Step 6:** Pull the plastic cover off the panel PC.
 - Step 7:** Make sure all the components listed in the packing list are present.

2.2 Packing List

The PPC-51xxA-H61 panel PC is shipped with the following components:


Quantity	Item	Image
1	PPC-51xxA-H61	
1	SATA CD-ROM cable (P/N: 32803-000300-100-RS)	
1	Power cord (P/N: 32000-000002-RS)	
1	Panel mounting kit (P/N: 19Z00-000024-RS)	
1	Wall mounting kit (P/N: 41020-016102-00-RS)	
1	Touch pen	
1	User manual and driver CD	
1	One Key Recovery CD	

Table 2-1: Packing List

If any of the above items are missing or damaged, contact the distributor or sales representative immediately.

2.3 Optional Items

The following items are optional accessories for the PPC-51xxA-H61:

Item	Image
Slim type SATA DVD-ROM (P/N: 73400-AD7760H01-RS)	
1-slot PCI riser card (P/N: PCIR-01H-R10)	
1-slot PCIe x1 riser card (P/N: PCIER-101H-R10)	
Arm (P/N: ARM-31-RS)	
Stand (P/N: STAND-210-R11)	
Gigabit Ethernet SFP fiber module (P/N: SFP1G-SX/-I SFP1G-MLX/-I SFP1G-LX10/-I SFP1G-ZX70/-I)	

PPC-51xxA-H61 Panel PC

Item	Image
Rack mounting kit (P/N: RK-150MS-R10 RK-170MS-R10 RK-190MS-R10)	
Wi-Fi module with RF cable and antenna for PPC-5150A-H61/PPC-5170A-H61, 2T2R, 802.11b/g/n (P/N: PPC-WL-KIT02-R10)	
Wi-Fi module with RF cable and antenna for PPC-5190A-H61, 2T2R, 802.11b/g/n (P/N: PPC-WL-KIT03-R10)	

Table 2-2: Optional Items

Chapter

3

Installation

3.1 Anti-static Precautions



WARNING:

Failure to take ESD precautions during the maintenance of the EP series may result in permanent damage to the EP series and severe injury to the user.

Electrostatic discharge (ESD) can cause serious damage to electronic components, including the PPC-51xxA-H61. Dry climates are especially susceptible to ESD. It is therefore critical that whenever the PPC-51xxA-H61 is accessed internally, or any other electrical component is handled, the following anti-static precautions are strictly adhered to.

- ***Wear an anti-static wristband:*** - Wearing a simple anti-static wristband can help to prevent ESD from damaging the board.
- ***Self-grounding:*** - Before handling the board touch any grounded conducting material. During the time the board is handled, frequently touch any conducting materials that are connected to the ground.
- ***Use an anti-static pad:*** - When configuring the PPC-51xxA-H61, place it on an anti-static pad. This reduces the possibility of ESD damaging the PPC-51xxA-H61.
- ***Only handle the edges of the PCB:*** - When handling the PCB, hold the PCB by the edges.

3.2 Installation Precautions

When installing the panel PC, please follow the precautions listed below:

- ***Power turned off:*** When installing the panel PC, make sure the power is off. Failing to turn off the power may cause severe injury to the body and/or damage to the system.
- ***Certified Engineers:*** Only certified engineers should install and modify onboard functionalities.

- **Mounting:** The PPC-51xxA-H61 is a heavy device. When mounting the system onto a rack, panel, wall or arm, please make sure that at least two people are assisting with the procedure.
- **Anti-static Discharge:** If a user open the rear panel of the panel PC, to configure the jumpers or plug in added peripheral devices, ground themselves first and wear and anti-static wristband.

3.3 Preinstalled Components

The following components are all preinstalled.

- Motherboard
- DDR3 memory module
- TFT LCD
- Touchscreen
- Power supply
- Inverter board
- System cooling fans

Preinstalled OEM customizations may include the following.

- CPU
- HDD
- Wi-Fi module
- Optical disk drive
- PCI/PCIe x1 riser card

3.4 Installation and Configuration Steps

The following installation steps must be followed.

Step 1: Unpack the PPC-51xxA-H61.

Step 2: Set the jumper settings.

Step 3: Install HDD, CompactFlash® card and optical disk drive.

Step 4: Mount the PPC-51xxA-H61 panel PC.

PPC-51xxA-H61 Panel PC

Step 5: Connect peripheral devices to the bottom panel of the PPC-51xxA-H61.

Step 6: Configure the system.

3.5 Removing the Back Cover

Remove all the retention screws on the back cover. Lift the cover up to remove.





Figure 3-1: PPC-5150A-H61 Back Cover Retention Screws

3.6 Jumper Settings



NOTE:

A jumper is a metal bridge used to close an electrical circuit. It consists of two or three metal pins and a small metal clip (often protected by a plastic cover) that slides over the pins to connect them. To CLOSE/SHORT a jumper means connecting the pins of the jumper with the plastic clip and to OPEN a jumper means removing the plastic clip from a jumper.



The following jumpers can be found on the motherboard installed in the PPC-51xxA-H61. Before the PPC-51xxA-H61 is installed, the jumpers must be set in accordance with the desired configuration. The jumpers on the PPC-51xxA-H61 motherboard are listed in **Table 3-1**.

Description	Label	Type
COM1 Pin 9 setting	J_COM_V1	6-pin header
COM2 Pin 9 setting	J_COM_V2	6-pin header
COM3 Pin 9 setting	J_COM_V3	6-pin header
COM4 Pin 9 setting	J_COM_V4	6-pin header
COM5 Pin 9 setting	J_COM_V5	6-pin header
COM5 RS-232/422/485 selection	JP2	4-pin header

Table 3-1: Jumpers

3.6.1 Access the Jumpers

To access the jumpers, remove the back cover. To remove the back cover, please refer to **Section 3.5**.

3.6.2 Preconfigured Jumpers



WARNING:

Do not change the settings on the jumpers in described here. Doing so may disable or damage the system

The following jumpers are preconfigured for the PPC-51xxA-H61. Users should not change these jumpers.

Jumper Name	Label	Type
CF card power selection	JP1	3-pin header
Inverter brightness voltage selection	J_ADJ1	3-pin header
LCD power selection	JLCD_PWR1	6-pin header
Panel type and resolution selection	JLCD_SET1	8-pin header
Touchscreen selection	JTOUCH1	4-pin header
USB1~USB4 power selection	USBAB_PWR1, USB01_PWR1, USB23_PWR1, USB45_PWR1	3-pin header

Table 3-2: Preconfigured Jumpers

3.6.3 COM1 to COM5 Pin 9 Setting Jumpers

Jumper Label: J_COM_V1, J_COM_V2, J_COM_V3, J_COM_V4 and J_COM_V5

Jumper Type: 6-pin header

Jumper Settings: See Table 3-3

Jumper Location: See Figure 3-2

Five jumpers configure pin 9 on the COM1, COM2, COM3, COM4 and COM5 connectors. Pin 9 on these connectors can be set as either +5 V, +12 V or as the ring (RI) signal. The COM1, COM2, COM3, COM4 and COM5 Pin 9 setting jumper selection options are shown in **Table 3-3**.

	Serial Port	Short 1 – 3	Short 2 - 4	Short 3 – 5	Short 4 – 6
		Default	Default		
J_COM_V1	COM1	RI signal	+5 V	Pin 9 power	+12 V
J_COM_V2	COM2	RI signal	+5 V	Pin 9 power	+12 V
J_COM_V3	COM3	RI signal	+5 V	Pin 9 power	+12 V
J_COM_V4	COM4	RI signal	+5 V	Pin 9 power	+12 V
J_COM_V5	COM5	RI signal	+5 V	Pin 9 power	+12 V

Table 3-3: COM1 to COM5 Pin 9 Setting Jumper Settings

The COM1 to COM5 Pin 9 setting jumper locations are shown in **Figure 3-2** below.




Figure 3-2: COM1 to COM5 Pin 9 Setting Jumper Locations

PPC-51xxA-H61 Panel PC

3.6.4 COM5 RS-232/422/485 Serial Port Selection Jumper

- Jumper Label: JP2
Jumper Type: 4-pin header
Jumper Settings: See Table 3-4
Jumper Location: See Figure 3-3

The COM5 RS-232/422/485 Serial Port Selection jumper sets the communication protocol used by the COM5 serial communications port as RS-232, RS-422 or RS-485. The COM5 RS-232/422/485 Serial Port Selection settings are shown in **Table 3-4**.

COM5 Mode	Pin 1-2	Pin 3-4
RS-232 (Default)	Short	Open
RS-422	Short	Short
RS-485 (Default: RX)	Open	Short
RS-485 (Default: TX)	Open	Open

Table 3-4: COM5 RS-232/422/485 Serial Port Selection Jumper Settings

The COM5 RS-232/422/485 Serial Port Select jumper location is shown in **Figure 3-3**.




Figure 3-3: COM5 RS-232/422/485 Serial Port Selection Jumper Location

3.7 Drive Installation

The drive installation process is shown in the sections below.

3.7.1 Hard Drive Installation

To install a HDD, please follow the steps below:

Step 1: Remove the back cover ([Section 3.5](#)).

Step 2: The HDD bracket is attached to the elevated platform by four retention screws.

Remove the four retention screws from the elevated platform ([Figure 3-4](#)).






Figure 3-4: HDD Bracket Retention Screws

Step 3: Attach the hard drive in the bracket. To do this, slide the hard drive onto the bracket until it connects with the SATA connector at the back. Fasten the four retention screws on the side.

PPC-51xxA-H61 Panel PC**Figure 3-5: HDD Retention Screws**

Step 4: Install the hard drive bracket (with hard drive and SATA cable attached) into the PPC-51xxA-H61 and fasten the four hard drive bracket screws.

**Figure 3-6: Replacing the HDD Bracket**

3.7.2 CompactFlash® Card Installation

To install the CompactFlash® card, please follow the steps below:

- Step 1:** Undo the CompactFlash® slot cover screw and remove the CompactFlash® cover plate.



Figure 3-7: CompactFlash® Cover Plate

- Step 2:** Insert the CompactFlash® card into the slot.



Figure 3-8: Installing the CompactFlash® Card

PPC-51xxA-H61 Panel PC

Step 3: Replace the CompactFlash® cover plate.



Figure 3-9: Replacing the CompactFlash® Cover Plate

3.7.3 Optical Disk Drive Installation (Optional)

To install an optical disk drive, please follow the steps below.

Step 1: Remove the back cover ([Section 3.5](#)).

Step 2: Undo the optical drive bracket screws and remove the optical drive bracket.




Figure 3-10: Optical Drive Bracket Retention Screws

Step 3: Remove the four screws from the optical drive bracket assembly (**Figure 3-11**).

Remove the blank drive plate.





Figure 3-11: Optical Drive Blank Plate Assembly

Step 4: Install the optical drive in the same position as the previously removed blank optical drive plate. Fasten the same four screws to attach the optical drive to the bracket.

PPC-51xxA-H61 Panel PC**Figure 3-12: Optical Drive Screws**

Step 5: Attach the SATA cable to the back of the optical drive and fasten the SATA cable screws.

**Figure 3-13: Optical Drive SATA Cable**

Step 6: Reinstall the optical drive bracket into the PPC-51xxA-H61 and fasten the optical bracket screws.




Figure 3-14: Replacing the Optical Drive Bracket

3.8 PCI Expansion Card Installation (Optional)



NOTE:

The expansion card cannot exceed the dimensions shown below.

HEIGHT LIMIT 25MM

HEIGHT LIMIT 15MM

100.00

22.00

3.22

12.06

IO AREA

89.90

10.96

To install a PCI expansion card, please do the following.

Step 1: Remove the back cover. See **Section 3.5**.

Step 2: Install the PCI riser card. Insert the PCI riser card into the PCI slot on the motherboard of the system. Secure the PCI riser card to the system with two retention screws.




Figure 3-15: Installing the PCI Riser Card

Step 3: Remove the expansion slot cover. The expansion slot on the I/O panel interface is secured to the system with a single retention screw. Remove the screw (Figure 3-16).



Figure 3-16: Expansion Slot Retention Screw

Step 4: Insert the expansion card. Align the PCI expansion card edge connector with the PCI expansion slot on the PCI riser card. Gently insert the PCI card into the PCI expansion slot.

PPC-51xxA-H61 Panel PC

Step 5: Secure the expansion card. Once the PCI card is correctly installed in the system, reinsert the previously removed retention screw to secure the card to the I/O interface panel.




Figure 3-17: Installing the PCI Card

3.9 PCIe Expansion Card Installation (Optional)



NOTE:

The expansion card cannot exceed the dimensions shown below.



To install a PCIe expansion card, please do the following.

Step 1: Remove the back cover. See [Section 3.5](#).

Step 2: Install the PCIe riser card. Insert the PCIe riser card into the PCI slot and PCIe x4 slot on the motherboard of the system. Secure the PCIe riser card to the system with two retention screws.

PPC-51xxA-H61 Panel PC



Figure 3-18: Installing the PCIe Riser Card

Step 3: Remove the expansion slot cover. The expansion slot on the I/O panel interface is secured to the system with a single retention screw. Remove the screw.



Figure 3-19: Expansion Slot Retention Screw

Step 4: Insert the expansion card. Align the PCIe expansion card edge connector with the PCIe expansion slot on the PCIe riser card. Gently insert the PCIe card into the PCIe expansion slot.

Step 5: Secure the expansion card. Once the PCIe card is correctly installed in the system, reinsert the previously removed retention screw to secure the card to the I/O interface panel.



Figure 3-20: Installing the PCIe Card

3.10 AT/ATX Mode Selection

AT and ATX power modes can both be used on the PPC-51xxA-H61 panel PC. The selection is made through an AT/ATX switch on the I/O interface panel. The switch is shown below.




Figure 3-21: AT/ATX Mode Selection

3.11 Mounting the System



WARNING!

When mounting the PPC-51xxA-H61 panel PC, it is advisable to have more than one person help with the installation to prevent accidental damage to the panel and avoid personal injury.

The methods of mounting the PPC-51xxA-H61 are:

- Wall mounting
- Panel mounting
- Arm mounting
- Stand mounting
- Rack mounting

The mounting methods are described in the following sections.

3.11.1 Wall Mounting

To mount the PPC-51xxA-H61 panel PC onto a wall, please follow the steps below.

Step 1: Select the location on the wall for the wall-mounting bracket.

Step 2: Carefully mark the locations of the four bracket screw holes on the wall.

Step 3: Drill four pilot holes at the marked locations on the wall for the bracket retention screws.

Step 4: Align the wall-mounting bracket screw holes with the pilot holes.

Step 5: Secure the mounting bracket to the wall by inserting the retention screws into the four pilot holes and tightening them (**Figure 3-22**).




Figure 3-22: Wall-mounting Bracket

Step 6: Insert the four monitor mounting screws provided in the wall mounting kit into the four screw holes on the rear panel of the monitor and tighten until the screw shank is secured against the rear panel (**Figure 3-23**).

Step 7: Align the mounting screws on the monitor rear panel with the mounting holes on the bracket.

Step 8: Carefully insert the screws through the holes and gently pull the monitor downwards until the monitor rests securely in the slotted holes (**Figure 3-23**). Ensure that all four of the mounting screws fit snugly into their respective slotted holes.



NOTE:

In the diagram below the bracket is already installed on the wall.




Figure 3-23: Mount the Chassis

Step 9: Secure the panel PC with the wall-mounting kit. To do this, stick the protective cushion to the wall-mounting kit first. Then, put the wall-mounting kit on the top panel of the panel PC. Carefully mark the location of the wall-mounting kit screw holes on the wall. Drill a pilot hole at the marked location on the wall. Secure the wall-mounting kit to the wall by inserting a retention screw into the pilot hole on the wall (**Figure 3-24**). This step is to avoid the panel PC being pushed apart from the wall-mounting bracket accidentally.




Figure 3-24: Secure the Chassis

3.11.2 Panel Mounting

To mount the PPC-51xxA-H61 panel PC into a panel, please follow the steps below.



NOTE:

The maximum panel thickness should be no more than 6 mm.

Step 1: Select the position on the panel to mount the PPC-51xxA-H61.

Step 2: Cut out a section of the panel that corresponds to the rear panel dimensions of the PPC-51xxA-H61. The recommended cutout sizes are shown below (**Figure 3-25**, **Figure 3-26** and **Figure 3-27**).

PPC-51xxA-H61 Panel PC




Figure 3-25: PPC-5150A-H61 Panel Cutout Dimensions




Figure 3-26: PPC-5170A-H61 Panel Cutout Dimensions




Figure 3-27: PPC-5190A-H61 Panel Cutout Dimensions

Step 3: Slide the PPC-51xxA-H61 through the hole until the metal frame is flush against the panel.

Step 4: Insert the panel mounting clamps into the pre-formed holes along the edges of the PPC-51xxA-H61, behind the aluminum frame (**Figure 3-28**). Refer to the mounting kit packing list for the required number of mounting clamps.




Figure 3-28: Panel Mounting Clamp Positions

Step 5: Tighten the screws that pass through the panel mounting clamps until the plastic caps at the front of all the screws are firmly secured to the panel (**Figure 3-29**).

PPC-51xxA-H61 Panel PC




Figure 3-29: Tighten the Panel Mounting Clamp Screws

3.11.3 Rack and Cabinet Installation

To mount the PPC-51xxA-H61 into a rack/cabinet, please follow the steps below.

Step 1: Secure the rack mounting bracket to two sides of the monitor using the supplied retention screws. Each bracket requires four screws.

Step 2: Secure the rack mounting bracket to the rack by inserting and tightening the supplied mounting nuts and bolts. Each bracket requires three nuts and bolts for installation.

3.11.4 Arm Mounting

The PPC-51xxA-H61 is VESA (Video Electronics Standards Association) compliant and can be mounted on an arm with a 100 mm interface pad. To mount the PPC-51xxA-H61 on an arm, please follow the steps below.

Step 1: The arm is a separately purchased item. Please correctly mount the arm onto the surface it uses as a base. To do this, refer to the installation documentation that came with the mounting arm.

**NOTE:**

When purchasing the arm please ensure that it is VESA compliant and that the arm has a 100 mm interface pad. If the mounting arm is not VESA compliant, it cannot be used to support the PPC-51xxA-H61 panel PC.

Step 2: Once the mounting arm has been firmly attached to its surface, lift the PPC-51xxA-H61 panel PC onto the interface pad of the mounting arm.

Step 3: Align the retention screw holes on the mounting arm interface with those in the PPC-51xxA-H61 panel PC. The arm mounting retention screw holes of the PPC-51xxA-H61 panel PC are shown in **Figure 3-30**.




Figure 3-30: Arm Mounting Retention Screw Holes

Step 4: Secure the PPC-51xxA-H61 to the interface pad by inserting four retention screws through the mounting arm interface pad and into the PPC-51xxA-H61 panel PC.

3.11.5 Stand Mounting

To mount the PPC-51xxA-H61 using the stand mounting kit, please follow the steps below.

PPC-51xxA-H61 Panel PC

Step 1: Locate the screw holes on the rear of the PPC-51xxA-H61. This is where the bracket will be attached.




Figure 3-31: Stand Mounting Retention Screw Holes

Step 2: Align the bracket with the screw holes.

Step 3: To secure the bracket to the PPC-51xxA-H61, insert the retention screws into the screw holes and tighten them.

3.12 SFP Fiber Module Installation (Optional)

To install the SFP fiber module, please follow the steps below:

Step 1: Locate the SFP fiber connectors. The locations of the connectors are shown in **Figure 1-5** and **Figure 1-6**.

Step 2: Align the SFP fiber module with one of the SFP fiber connectors on the PPC-51xxA-H61 (**Figure 3-32**).

Step 3: Once aligned, slide the SFP module into place (**Figure 3-32**).



Figure 3-32: SFP Fiber Module Installation



NOTE:

The pin locations of the SFP connector 2 are opposite to the SFP connector 1. Please rotate the SFP module to a proper position to install the SFP module into the SFP connector 2.

3.13 Bottom Panel Connectors

The bottom panel of the PPC-51xxA-H61 contains I/O connectors, switches and a CF card slot. Detailed descriptions of the connectors can be found in the subsections below.

3.13.1 Audio Connectors

The audio jacks connect to external audio devices.

- **Mic-in (Pink):** Connects a microphone.
- **Line-out (Green):** Connects to a headphone or a speaker. With multi-channel configurations, this port can also connect to front speakers.

3.13.2 RJ-45 LAN Connectors

The RJ-45 LAN connectors allow connections to external networks. The pinouts of the RJ-45 LAN connector is shown below.

Pin	Description	Pin	Description
1	MDIA3-	2	MDIA3+
3	MDIA2-	4	MDIA1-
5	MDIA1+	6	MDIA2+
7	MDIA0-	8	MDIA0+

Table 3-5: LAN Pinouts




Figure 3-33: RJ-45 LAN Connector

Each RJ-45 LAN connector has two status LEDs, one green and one yellow. See Figure 3-33.

LED	Description	LED	Description
A	on: linked blinking: data is being sent/received	B	off: 10 Mb/s green: 100 Mb/s orange: 1000 Mb/s

Table 3-6: RJ-45 LAN Connector LEDs

To connect the PPC-51xxA-H61 to a network through the RJ-45 LAN connectors, follow the steps below.

Step 1: Locate the RJ-45 connectors. The locations of the RJ-45 connectors are shown in **Figure 1-5** and **Figure 1-6**.

Step 2: Align the connectors. Align the RJ-45 connector on the LAN cable with one of the RJ-45 connectors on the PPC-51xxA-H61. See **Figure 3-34**.




Figure 3-34: LAN Connection

Step 3: Insert the LAN cable RJ-45 connector. Once aligned, gently insert the LAN cable RJ-45 connector into the on-board RJ-45 connector.

3.13.3 RS-232 Serial Ports (COM1, COM2, COM3, COM4)

CN Label: COM1, COM2, COM3, COM4

CN Type: DB-9 connector

CN Location: See [Figure 1-5](#) and [Figure 1-6](#)

CN Pinouts: See [Table 3-7](#) and [Figure 3-35](#)

An RS-232 device can be connected to the RS-232 serial port on the bottom panel. The pinouts of the RS-232 serial port is shown below.




Figure 3-35: RS-232 Serial Port

PPC-51xxA-H61 Panel PC

Pin	Description
1	DCD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

Table 3-7: RS-232 Serial Port Pinouts

To install the RS-232 devices, follow the steps below.

Step 1: Locate the DB-9 connector. The locations of the DB-9 connectors are shown in **Figure 1-5** and **Figure 1-6**.

Step 2: Insert the serial connector. Insert the DB-9 connector of a serial device into the DB-9 connector on the external peripheral interface. See **Figure 3-36**.




Figure 3-36: RS-232 Serial Device Connector

Step 3: Secure the connector. Secure the serial device connector to the external interface by tightening the two retention screws on either side of the connector.

3.13.4 RS-232/422/485 Serial Port (COM5)

CN Label: COM5

CN Type: DB-9 connector

CN Location: See **Figure 1-5**

CN Pinouts: See **Table 3-8 and Figure 3-37**

An RS-232/422/485 device can be connected to the RS-232/422/485 serial port on the bottom panel. The pinouts of the RS-232/422/485 serial port is shown below.




Figure 3-37: RS-232/422/485 Serial Port

Pin	RS-232	RS-422	RS-485
1	-NDCD	TXD422#	TXD485#
2	NSIN	TXD422+	TXD485+
3	NSOUT	RXD422+	
4	-NDTR	RXD422#	
5	GND		
6	-NDSR		
7	-NRTS		
8	-NCTS		
9	COMPIN9		

Table 3-8: RS-232/422/485 Serial Port Pinouts

To install the RS-232/422/485 devices, follow the steps below.

Step 1: Locate the DB-9 connector. The location of the DB-9 connector is shown in **Figure 1-5 and Figure 1-6**.

PPC-51xxA-H61 Panel PC

Step 2: Insert the serial connector. Insert the DB-9 connector of a serial device into the DB-9 connector on the external peripheral interface. See **Figure 3-38**.




Figure 3-38: RS-232/422/485 Serial Device Connector

Step 3: Secure the connector. Secure the serial device connector to the external interface by tightening the two retention screws on either side of the connector.

3.13.5 SFP Fiber LAN Connectors

The PPC-51xxA-H61 has two SFP fiber LAN connectors. The locations of the connectors are shown in **Figure 1-5** and **Figure 1-6**. To install an SFP module, refer to **Section 3.12**.

3.13.6 USB 2.0 Connectors

The USB 2.0 ports are for attaching USB 2.0/1.1 peripheral devices to the system. The pinouts of the USB 2.0 port is shown below.

Pin	Description
1	VCC
2	DATA-
3	DATA+
4	GROUND

Table 3-9: USB 2.0 Port Pinouts

To connect a USB 2.0 or USB 1.1 device, please follow the instructions below.

Step 1: Located the USB connectors. The locations of the USB connectors are shown in Chapter 1.

Step 2: Align the connectors. Align the USB device connector with one of the connectors on the bottom panel. See **Figure 3-39**.




Figure 3-39: USB Device Connection

Step 3: Insert the device connector. Once aligned, gently insert the USB device connector into the onboard connector.

3.13.7 USB 3.0 Connectors

The USB 3.0 ports are for attaching USB 3.0 peripheral devices to the system. The pinouts of the USB 3.0 port is shown below.

Pin	Description	Pin	Description
1	USB3_PWR1	10	USB3_PWR2
2	USB2PO_DM1	11	USB2PO_DM2
3	USB2PO_DP1	12	USB2PO_DP2
4	GND	13	GND
5	USB3PO_RXDN1	14	USB3PO_RXDN2

PPC-51xxA-H61 Panel PC

Pin	Description	Pin	Description
6	USB3PO_RXDP1	15	USB3PO_RXDP2
7	GND	16	GND
8	USB3PO_TXDN1	17	USB3PO_TXDN2
9	USB3PO_TXDP1	18	USB3PO_TXDP2

Table 3-10: USB 3.0 Port Pinouts

3.13.8 VGA Connector

The VGA connector connects to a monitor that accepts VGA video input. The pinouts of the VGA connector is shown below.




Figure 3-40: VGA Connector

Pin	Description	Pin	Description
1	RED	2	GREEN
3	BLUE	4	NC
5	GND	6	GND
7	GND	8	GND
9	5V	10	GND
11	NC	12	DDCDAT
13	HSYNC	14	VSYNC
15	DDCCLK		

Table 3-11: VGA Connector Pinouts

To connect the PPC-51xxA-H61 to a second display, follow the steps below,

Step 1: Locate the female DB-15 connector. The location of the female DB-15 connector is shown in **Figure 1-5** and **Figure 1-6**.

Step 2: **Align the VGA connector.** Align the male DB-15 connector on the VGA screen cable with the female DB-15 connector on the external peripheral interface.

Step 3: **Insert the VGA connector.** Once the connectors are properly aligned with the insert the male connector from the VGA screen into the female connector on the PPC-51xxA-H61. See **Figure 3-41**.




Figure 3-41: VGA Connector

3.14 Driver Installation



NOTE:

The content of the CD may vary throughout the life cycle of the product and is subject to change without prior notice. Visit the IEI website or contact technical support for the latest updates.

All the drivers for the PPC-51xxA-H61 are on the CD that came with the system. To install the drivers, please follow the steps below.

Step 1: Insert the CD into an optical disk drive connected to the system.

PPC-51xxA-H61 Panel PC**NOTE:**

If the installation program doesn't start automatically:

Click "Start->My Computer->CD Drive->autorun.exe"

Step 2: The driver main menu appears (**Figure 3-42**).



Figure 3-42: Driver Menu

Step 3: Install all of the necessary drivers in this menu.

Chapter

4

System Maintenance

4.1 System Maintenance Introduction

The following system components may require maintenance.

- Motherboard
- SO-DIMM module
- PSU module
- Cooling fans

If these components fail, they must be replaced. Please contact the system reseller or vendor to purchase replacement parts. Replacement instructions for the above listed components are described below.

4.2 Motherboard Replacement

A user cannot replace a motherboard. If the motherboard fails it must be shipped back to IEI to be replaced. If the system motherboard has failed, please contact the system vendor, reseller or an IEI sales person directly.

4.3 Back Cover Removal



WARNING!

Before removing the back cover, make sure all power to the system has been disconnected. Failing to do so may cause severe damage to the PPC-51xxA-H61 and injury to the user.

**WARNING!**

Please take anti-static precautions when working with the internal components. The interior of the PPC-51xxA-H61 contains very sensitive electronic components. These components are easily damaged by electrostatic discharge (ESD). Before working with the internal components, make sure all anti-static precautions described earlier have been observed.

To access the panel PC internal components, the back cover must be removed. To remove the back cover, please refer to **Section 3.5** for back cover removal instructions.

4.4 SO-DIMM Replacement

Please read the warnings at the beginning of the previous section before attempting to access any PPC-51xxA-H61 internal components.

To install/replace the SO-DIMM modules, please follow the steps below.

Step 1: Remove the back cover (**Section 3.5**).

Step 2: Locate the SO-DIMM module on the motherboard.




Figure 4-1: SO-DIMM Module Locations

PPC-51xxA-H61 Panel PC

Step 3: Release the SO-DIMM module by pulling both the spring retainer clips outward from the socket.

Step 4: Grasp the SO-DIMM module by the edges and carefully pull it out of the socket.

Step 5: Install the new SO-DIMM module by pushing it into the socket at an angle (**Figure 4-2**).

Step 6: Gently push the rear of the SO-DIMM module down (**Figure 4-2**). The spring retainer clips clip into place and secure the SO-DIMM module in the socket.




Figure 4-2: SO-DIMM Module Installation

4.5 Elevated Platform Removal

The elevated platform supports the optical drive and the hard drive. It is not necessary to remove the hard drive bracket to remove the elevated platform.

Step 1: Unfasten the elevated platform screws on the top panel (**Figure 4-3**).



Figure 4-3: PPC-5150A-H61 Top Panel Elevated Platform Screws

Step 2: Unfasten the elevated platform screws on the side panel (**Figure 4-4**).



Figure 4-4: PPC-5150A-H61 Side Panel Elevated Platform Screws

Step 3: Unfasten the elevated platform screws on the bottom panel (**Figure 4-5**).



Figure 4-5: PPC-5150A-H61 Bottom Panel Elevated Platform Screws

Step 4: Unfasten the internal elevated platform screws (**Figure 4-6**).



Figure 4-6: PPC-5150A-H61 Internal Elevated Platform Screws

Step 5: Slide the elevated platform out of the chassis.

4.6 PSU Module Replacement

Please read the warnings at the beginning of **Section 4.3** before attempting to access any PPC-51xxA-H61 internal components.

If the PSU module has been damaged it must be replaced. To replace the PSU module, please follow the steps below.

4.6.1 Remove the Old PSU

Step 1: Remove the back cover (**Section 3.5**).

Step 2: Detach and remove the elevated platform (**Section 4.5**).

Step 3: Disconnect all PSU connections including those to the motherboard (**Figure 4-7**) and any disk drives.




Figure 4-7: PSU Power Cables

Step 4: Unfasten the screws on the inside panel (**Figure 4-8**).




Figure 4-8: PSU Bottom Panel Retention Screws

Step 5: Remove the retention screws that connect the PSU bracket to the chassis (**Figure 4-9**).



Figure 4-9: PSU Bottom Panel Screws

Step 6: Remove the retention screws that connect the PSU to the PSU bracket.

4.6.2 Install the New PSU

Installation is done in the reverse order to removal. To install a new PSU module, please follow the steps below.

Step 1: Attach the PSU bracket to the PSU module with the previously removed retention screws.

Step 2: Insert the PSU module and bracket assembly into the chassis and attach the PSU bracket to the chassis with the previously removed retention screws.

PPC-51xxA-H61 Panel PC

Step 3: Secure the PSU module to the chassis by reinserting the previously removed retention screws through the bottom panel.

Step 4: Bundle the cables of the new PSU module and secure them with a plastic tie similar to the old PSU module.

Step 5: Reconnect all previously disconnected power connectors to the motherboard and disk drives.

Step 6: Reattach the elevated platform.

Step 7: Replace the back cover.

4.7 System Cooling Fan Replacement

If the system cooling fans have been damaged, they must be replaced. To replace the system cooling fans, please follow the steps below.

4.7.1 Remove the Old System Cooling Fans

Step 1: Remove the back cover ([Section 3.5](#)).

Step 2: Disconnect the system cooling fans from the motherboard ([Figure 4-10](#)).




Figure 4-10: System Cooling Fans Motherboard Connector

- Step 3:** Remove the system cooling fans retention screws from the left panel
(Figure 4-11).



Figure 4-11: System Cooling Fans Left Panel Retention Screws

- Step 4:** Remove the system cooling fans from the chassis.

4.7.2 Install the New System Cooling Fans

To install the new system cooling fans, please follow the steps below.

- Step 1:** Insert the system cooling fans into the chassis and attach to the left panel with the previously removed retention screws.
- Step 2:** Rebundle the new fan wires and tie them to the chassis like the old fan wires.
- Step 3:** Reconnect the new fan connector to the motherboard.
- Step 4:** Replace the back cover.

Chapter

5

BIOS Setup

5.1 Introduction

The BIOS is programmed onto the BIOS chip. The BIOS setup program allows changes to certain system settings. This chapter outlines the options that can be changed.



NOTE:

Some of the BIOS options may vary throughout the life cycle of the product and are subject to change without prior notice.

5.1.1 Starting Setup

The UEFI BIOS is activated when the computer is turned on. The setup program can be activated in one of two ways.

1. Press the **DELETE** or **F2** key as soon as the system is turned on or
2. Press the **DELETE** or **F2** key when the “**Press DELETE or F2 to enter SETUP**” message appears on the screen.

If the message disappears before the **DELETE** or **F2** key is pressed, restart the computer and try again.

5.1.2 Using Setup

Use the arrow keys to highlight items, press **ENTER** to select, use the **PageUp** and **PageDown** keys to change entries, press **F1** for help and press **Esc** to quit. Navigation keys are shown in the following table.

Key	Function
Up arrow	Move to the item above
Down arrow	Move to the item below
Left arrow	Move to the item on the left hand side
Right arrow	Move to the item on the right hand side
+	Increase the numeric value or make changes

PPC-51xxA-H61 Panel PC

Key	Function
-	Decrease the numeric value or make changes
Page up	Move to the next page
Page down	Move to the previous page
Esc	Main Menu – Quit and do not save changes into CMOS Status Page Setup Menu and Option Page Setup Menu -- Exit current page and return to Main Menu
F1	General help, only for Status Page Setup Menu and Option Page Setup Menu
F2	Load previous values
F3	Load optimized defaults
F4	Save changes and Exit BIOS

Table 5-1: BIOS Navigation Keys

5.1.3 Getting Help

When **F1** is pressed a small help window describing the appropriate keys to use and the possible selections for the highlighted item appears. To exit the Help Window press **Esc** or the **F1** key again.

5.1.4 Unable to Reboot after Configuration Changes

If the computer cannot boot after changes to the system configuration are made, press the CMOS button on the bottom panel to clear the CMOS data and reset the system BIOS information. The location of the CMOS button is shown in **Figure 1-5** and **Figure 1-6**.

5.1.5 BIOS Menu Bar

The **menu bar** on top of the BIOS screen has the following main items:

- Main – Changes the basic system configuration.
- Advanced – Changes the advanced system settings.
- Chipset – Changes the chipset settings.
- Boot – Changes the system boot configuration.


- Security – Sets User and Supervisor Passwords.
- Save & Exit – Selects exit options and loads default settings

The following sections completely describe the configuration options found in the menu items at the top of the BIOS screen and listed above.

5.2 Main

The **Main** BIOS menu (**BIOS Menu 1**) appears when the **BIOS Setup** program is entered.

The **Main** menu gives an overview of the basic system information.



BIOS Menu 1: Main

→ BIOS Information

The **BIOS Information** lists a brief summary of the BIOS. The fields in **BIOS Information** cannot be changed. The items shown in the system overview include:

- **BIOS Vendor:** Installed BIOS vendor
- **Core Version:** Current BIOS version
- **Compliance:** compliant UEFI specification version
- **Project Version:** the board version
- **Build Date and Time:** Date and time the current BIOS version was made

PPC-51xxA-H61 Panel PC

→ System Date [xx/xx/xx]

Use the **System Date** option to set the system date. Manually enter the day, month and year.

→ System Time [xx:xx:xx]

Use the **System Time** option to set the system time. Manually enter the hours, minutes and seconds.

5.3 Advanced

Use the **Advanced** menu (**BIOS Menu 2**) to configure the CPU and peripheral devices through the following sub-menus:



WARNING!

Setting the wrong values in the sections below may cause the system to malfunction. Make sure that the settings made are compatible with the hardware.

Aptio Setup Utility - Copyright (C) 2011 American Megatrends, Inc.

Main Advanced Chipset Boot Security Save & Exit

AMI Debug Rx Enabled!

> ACPI Settings
> RTC Wake Settings
> CPU Configuration
> SATA Configuration
> USB Configuration
> F81866 Super IO Configuration
> F81866 H/M Monitor
> Serial Port Console Redirection

System ACPI Parameters


→←: Select Screen
↑↓: Select Item
Enter: Select
+/-: Change Opt.
F1: General Help
F2: Previous Values
F3: Optimized Defaults
F4: Save & Exit
ESC: Exit

Version 2.14.1219. Copyright (C) 2011 American Megatrends, Inc.

BIOS Menu 2: Advanced

5.3.1 ACPI Settings

The **ACPI Settings** menu (**BIOS Menu 3**) configures the Advanced Configuration and Power Interface (ACPI) options.



BIOS Menu 3: ACPI Settings

→ **ACPI Sleep State [S1 only (CPU Stop Clock)]**


Use the **ACPI Sleep State** option to specify the sleep state the system enters when it is not being used.

- **S1 only (CPU Stop Clock)** **DEFAULT** The system enters S1(POS) sleep state. The system appears off. The CPU is stopped; RAM is refreshed; the system is running in a low power mode.

- **S3 only (Suspend to RAM)** The caches are flushed and the CPU is powered off. Power to the RAM is maintained. The computer returns slower to a working state, but more power is saved.

5.3.2 RTC Wake Settings

The **RTC Wake Settings** menu (**BIOS Menu 4**) enables the system to wake at the specified time.



BIOS Menu 4: RTC Wake Settings

→ Wake system with Fixed Time [Disabled]

Use the **Wake system with Fixed Time** option to enable or disable the system wake on alarm event.

→ **Disabled** **DEFAULT** The real time clock (RTC) cannot generate a wake event

→ **Enabled** If selected, the **Wake up every day** option appears allowing you to enable to disable the system to wake every day at the specified time. Besides, the following options appear with values that can be selected:

Wake up date

Wake up hour


Wake up minute

Wake up second

After setting the alarm, the computer turns itself on from a suspend state when the alarm goes off.

5.3.3 CPU Configuration

Use the **CPU Configuration** menu (**BIOS Menu 5**) to view detailed CPU specifications and configure the CPU.



BIOS Menu 5: CPU Configuration

The CPU Configuration menu (**BIOS Menu 5**) lists the following CPU details:

- CPU Signature: Lists the CPU signature value.
- Microcode Patch: Lists the microcode patch being used.
- Max CPU Speed: Lists the maximum CPU processing speed.
- Min CPU Speed: Lists the minimum CPU processing speed.
- CPU Speed: Lists the CPU processing speed.
- Processor Cores: Lists the number of the processor core

PPC-51xxA-H61 Panel PC

- Intel HT Technology: Indicates if Intel HT Technology is supported by the CPU.
- Intel VT-x Technology: Indicates if Intel VT-x Technology is supported by the CPU.
- Intel SMX Technology: Indicates if Intel SMX Technology is supported by the CPU.
- 64-bit: Indicates if 64-bit system is supported by the CPU.
- L1 Data Cache: Lists the amount of data storage space on the L1 cache.
- L1 Code Cache: Lists the amount of code storage space on the L1 cache.
- L2 Cache: Lists the amount of storage space on the L2 cache.
- L3 Cache: Lists the amount of storage space on the L3 cache.

→ Intel Virtualization Technology [Disabled]


Use the **Intel Virtualization Technology** option to enable or disable virtualization on the system. When combined with third party software, Intel® Virtualization technology allows several OSs to run on the same system at the same time.

→ **Disabled** **DEFAULT** Disables Intel Virtualization
Technology.

→ **Enabled** Enables Intel Virtualization Technology.

5.3.4 SATA Configuration

Use the **SATA Configuration** menu (**BIOS Menu 6**) to change and/or set the configuration of the SATA devices installed in the system.



BIOS Menu 6: SATA Configuration

→ **SATA Controller(s) [Enabled]**

Use the **SATA Controller(s)** option to configure the SATA controller(s).

→ **Enabled** **DEFAULT** Enables the on-board SATA controller(s).

→ **Disabled** Disables the on-board SATA controller(s).

→ **SATA Mode Selection [IDE]**


Use the **SATA Mode Selection** option to configure SATA devices as normal IDE devices.

→ **IDE** **DEFAULT** Configures SATA devices as normal IDE device.

→ **AHCI** The SATA drive connected to the nth SATA drive port is specified as a normal SATA drive.

5.3.5 USB Configuration

Use the **USB Configuration** menu (**BIOS Menu 7**) to read USB configuration information and configure the USB settings.



BIOS Menu 7: USB Configuration

→ USB Devices

The **USB Devices** field lists the USB devices that are enabled on the system

→ Legacy USB Support [Enabled]


Use the **Legacy USB Support** BIOS option to enable USB mouse and USB keyboard support. Normally if this option is not enabled, any attached USB mouse or USB keyboard does not become available until a USB compatible operating system is fully booted with all USB drivers loaded. When this option is enabled, any attached USB mouse or USB keyboard can control the system even when there is no USB driver loaded onto the system.

→ Enabled DEFAULT Legacy USB support enabled

- ➔ **Disabled** Legacy USB support disabled
- ➔ **Auto** Legacy USB support disabled if no USB devices are connected

5.3.6 F81866 Super IO Configuration


Use the **F81866 Super IO Configuration** menu (**BIOS Menu 8**) to set or change the configurations for the serial ports.



BIOS Menu 8: F81866 Super IO Configuration

5.3.6.1 Serial Port n Configuration

Use the **Serial Port n Configuration** menu (**BIOS Menu 9**) to configure the serial port n.



BIOS Menu 9: Serial Port n Configuration Menu

5.3.6.1.1 Serial Port 1 Configuration

→ **Serial Port [Enabled]**

Use the **Serial Port** option to enable or disable the serial port.

→ **Disabled** Disable the serial port

→ **Enabled** **DEFAULT** Enable the serial port

→ **Change Settings [Auto]**

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

→ **Auto** **DEFAULT** The serial port IO port address and interrupt address are automatically detected.

→ **IO=3F8h;
IRQ=4** Serial Port I/O port address is 3F8h and the interrupt address is IRQ4

- ➔ IO=3F8h;
IRQ=3, 4 Serial Port I/O port address is 3F8h and the interrupt address is IRQ3, 4
- ➔ IO=2F8h;
IRQ=3, 4 Serial Port I/O port address is 2F8h and the interrupt address is IRQ3, 4
- ➔ IO=2C0h;
IRQ=3, 4 Serial Port I/O port address is 2C0h and the interrupt address is IRQ3, 4
- ➔ IO=2C8h;
IRQ=3, 4 Serial Port I/O port address is 2C8h and the interrupt address is IRQ3, 4

5.3.6.1.2 Serial Port 2 Configuration

➔ **Serial Port [Enabled]**

Use the **Serial Port** option to enable or disable the serial port.

- ➔ **Disabled** Disable the serial port
- ➔ **Enabled** **DEFAULT** Enable the serial port

➔ **Change Settings [Auto]**

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

- ➔ **Auto** **DEFAULT** The serial port IO port address and interrupt address are automatically detected.
- ➔ IO=2F8h;
IRQ=3 Serial Port I/O port address is 2F8h and the interrupt address is IRQ3
- ➔ IO=3F8h;
IRQ=3, 4 Serial Port I/O port address is 3F8h and the interrupt address is IRQ3, 4
- ➔ IO=2F8h;
IRQ=3, 4 Serial Port I/O port address is 2F8h and the interrupt address is IRQ3, 4
- ➔ IO=2C0h;
IRQ=3, 4 Serial Port I/O port address is 2C0h and the interrupt address is IRQ3, 4

PPC-51xxA-H61 Panel PC

- IO=2C8h;
IRQ=3, 4 Serial Port I/O port address is 2C8h and the interrupt address is IRQ3, 4

5.3.6.1.3 Serial Port 3 Configuration

→ Serial Port [Enabled]

Use the **Serial Port** option to enable or disable the serial port.

- **Disabled** Disable the serial port
→ **Enabled** **DEFAULT** Enable the serial port

→ Change Settings [Auto]

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

- **Auto** **DEFAULT** The serial port IO port address and interrupt address are automatically detected.
→ **IO=3E8h;**
IRQ=10 Serial Port I/O port address is 3E8h and the interrupt address is IRQ10
→ **IO=3E8h;**
IRQ=10, 11 Serial Port I/O port address is 3E8h and the interrupt address is IRQ10, 11
→ **IO=2E8h;**
IRQ=10, 11 Serial Port I/O port address is 2E8h and the interrupt address is IRQ10, 11
→ **IO=2D0h;**
IRQ=10, 11 Serial Port I/O port address is 2D0h and the interrupt address is IRQ10, 11
→ **IO=2D8h;**
IRQ=10, 11 Serial Port I/O port address is 2D8h and the interrupt address is IRQ10, 11

5.3.6.1.4 Serial Port 4 Configuration

→ Serial Port [Enabled]

Use the **Serial Port** option to enable or disable the serial port.

→ **Disabled** Disable the serial port

→ **Enabled** **DEFAULT** Enable the serial port

→ Change Settings [Auto]

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

→ **Auto** **DEFAULT** The serial port IO port address and interrupt address are automatically detected.

→ **IO=2E8h;**
IRQ=10 Serial Port I/O port address is 2E8h and the interrupt address is IRQ10

→ **IO=3E8h;**
IRQ=10, 11 Serial Port I/O port address is 3E8h and the interrupt address is IRQ10, 11

→ **IO=2E8h;**
IRQ=10, 11 Serial Port I/O port address is 2E8h and the interrupt address is IRQ10, 11

→ **IO=2D0h;**
IRQ=10, 11 Serial Port I/O port address is 2D0h and the interrupt address is IRQ10, 11

→ **IO=2D8h;**
IRQ=10, 11 Serial Port I/O port address is 2D8h and the interrupt address is IRQ10, 11

5.3.6.1.5 Serial Port 5 Configuration

→ Serial Port [Enabled]

Use the **Serial Port** option to enable or disable the serial port.

PPC-51xxA-H61 Panel PC

- ➔ **Disabled** Disable the serial port
- ➔ **Enabled** **DEFAULT** Enable the serial port

➔ **Device Mode [Normal]**

The **Device Mode** option is used to set the Serial Port 5 signaling mode.

- ➔ **Normal** **DEFAULT** Sets the serial port mode to normal.
- ➔ **RS422/
RS485** Enables serial port RS-422/485 support.


➔ **Change Settings [Auto]**

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

- ➔ **Auto** **DEFAULT** The serial port IO port address and interrupt address are automatically detected.
- ➔ **IO=2D0h;
IRQ=10** Serial Port I/O port address is 2D0h and the interrupt address is IRQ10
- ➔ **IO=2C0h;
IRQ=10, 11** Serial Port I/O port address is 2C0h and the interrupt address is IRQ10, 11
- ➔ **IO=2C8h;
IRQ=10, 11** Serial Port I/O port address is 2C8h and the interrupt address is IRQ10, 11
- ➔ **IO=2D0h;
IRQ=10, 11** Serial Port I/O port address is 2D0h and the interrupt address is IRQ10, 11
- ➔ **IO=2D8h;
IRQ=10, 11** Serial Port I/O port address is 2D8h and the interrupt address is IRQ10, 11
- ➔ **IO=2E0h;
IRQ=10, 11** Serial Port I/O port address is 2E0h and the interrupt address is IRQ10, 11

5.3.7 F81866 H/W Monitor

The F81866 H/W Monitor menu (**BIOS Menu 10**) contains the fan configuration submenu and displays operating temperature and fan speeds.



BIOS Menu 10: F81866 H/W Monitor

→ PC Health Status

The following system parameters and values are shown. The system parameters that are monitored are:

- System Temperatures:
 - CPU Temperature
 - System Temperature
- Fan Speeds:
 - CPU_Fan1 Speed
 - SYS_Fan2 Speed
 - SYS_Fan3 Speed

5.3.7.1 Smart Fan Mode Configuration

Use the **Smart Fan Mode Configuration** submenu (**BIOS Menu 11**) to configure the fan temperature and speed settings.

PPC-51xxA-H61 Panel PC

Aptio Setup Utility - Copyright (C) 2011 American Megatrends, Inc.

Advanced																																																									
<table border="0"> <tr><td>Smart Fan Mode Configuration</td><td></td></tr> <tr><td>CPU_FAN1 Smart Fan control</td><td>[Auto Duty-Cycle Mode]</td></tr> <tr><td>CPU Temperature 1</td><td>60</td></tr> <tr><td>CPU Temperature 2</td><td>50</td></tr> <tr><td>CPU Temperature 3</td><td>40</td></tr> <tr><td>CPU Temperature 4</td><td>30</td></tr> <tr><td>Duty Cycle 1</td><td>100</td></tr> <tr><td>Duty Cycle 2</td><td>80</td></tr> <tr><td>Duty Cycle 3</td><td>70</td></tr> <tr><td>Duty Cycle 4</td><td>50</td></tr> <tr><td>SYS_FAN2 Smart Fan control</td><td>[Auto Duty-Cycle Mode]</td></tr> <tr><td>System Temperature 1</td><td>60</td></tr> <tr><td>System Temperature 2</td><td>50</td></tr> <tr><td>System Temperature 3</td><td>40</td></tr> <tr><td>System Temperature 4</td><td>30</td></tr> <tr><td>Duty Cycle 1</td><td>90</td></tr> <tr><td>Duty Cycle 2</td><td>60</td></tr> <tr><td>Duty Cycle 3</td><td>40</td></tr> <tr><td>Duty Cycle 4</td><td>10</td></tr> <tr><td>SYS_FAN3 Smart Fan control</td><td>[Auto Duty-Cycle Mode]</td></tr> <tr><td>Temperature 1</td><td>70</td></tr> <tr><td>Temperature 2</td><td>60</td></tr> <tr><td>Temperature 3</td><td>50</td></tr> <tr><td>Temperature 4</td><td>30</td></tr> <tr><td>Duty Cycle 1</td><td>90</td></tr> <tr><td>Duty Cycle 2</td><td>60</td></tr> <tr><td>Duty Cycle 3</td><td>40</td></tr> <tr><td>Duty Cycle 4</td><td>10</td></tr> </table>		Smart Fan Mode Configuration		CPU_FAN1 Smart Fan control	[Auto Duty-Cycle Mode]	CPU Temperature 1	60	CPU Temperature 2	50	CPU Temperature 3	40	CPU Temperature 4	30	Duty Cycle 1	100	Duty Cycle 2	80	Duty Cycle 3	70	Duty Cycle 4	50	SYS_FAN2 Smart Fan control	[Auto Duty-Cycle Mode]	System Temperature 1	60	System Temperature 2	50	System Temperature 3	40	System Temperature 4	30	Duty Cycle 1	90	Duty Cycle 2	60	Duty Cycle 3	40	Duty Cycle 4	10	SYS_FAN3 Smart Fan control	[Auto Duty-Cycle Mode]	Temperature 1	70	Temperature 2	60	Temperature 3	50	Temperature 4	30	Duty Cycle 1	90	Duty Cycle 2	60	Duty Cycle 3	40	Duty Cycle 4	10
Smart Fan Mode Configuration																																																									
CPU_FAN1 Smart Fan control	[Auto Duty-Cycle Mode]																																																								
CPU Temperature 1	60																																																								
CPU Temperature 2	50																																																								
CPU Temperature 3	40																																																								
CPU Temperature 4	30																																																								
Duty Cycle 1	100																																																								
Duty Cycle 2	80																																																								
Duty Cycle 3	70																																																								
Duty Cycle 4	50																																																								
SYS_FAN2 Smart Fan control	[Auto Duty-Cycle Mode]																																																								
System Temperature 1	60																																																								
System Temperature 2	50																																																								
System Temperature 3	40																																																								
System Temperature 4	30																																																								
Duty Cycle 1	90																																																								
Duty Cycle 2	60																																																								
Duty Cycle 3	40																																																								
Duty Cycle 4	10																																																								
SYS_FAN3 Smart Fan control	[Auto Duty-Cycle Mode]																																																								
Temperature 1	70																																																								
Temperature 2	60																																																								
Temperature 3	50																																																								
Temperature 4	30																																																								
Duty Cycle 1	90																																																								
Duty Cycle 2	60																																																								
Duty Cycle 3	40																																																								
Duty Cycle 4	10																																																								
Smart Fan Mode Select ----- →←: Select Screen ↑↓: Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit																																																									

Version 2.14.1219. Copyright (C) 2011 American Megatrends, Inc.

BIOS Menu 11: Smart Fan Mode Configuration**→ CPU_FAN1/SYS_FAN2/SYS_FAN3 Smart Fan Control [Auto by RPM]**

Use the **CPU_FAN1/SYS_FAN2/SYS_FAN3 Smart Fan Control** option to configure the smart fans.

- **Manual Duty Mode** The fan spins at the speed set in Manual Duty Mode settings.
- **Auto Duty-Cycle Mode** The fan adjusts its speed using Auto Duty-Cycle Mode settings.

→ CPU Temperature n/System Temperature n/Temperature n


Use the + or – key to change the temperature value. Enter a decimal number between 1 and 100.

→ Duty Cycle n

Use the + or – key to change the fan value in percentage. Enter a decimal number between 1 and 100.

5.3.8 Serial Port Console Redirection

The **Serial Port Console Redirection** menu (**BIOS Menu 12**) allows the console redirection options to be configured. Console redirection allows users to maintain a system remotely by re-directing keyboard input and text output through the serial port.



BIOS Menu 12: Serial Port Console Redirection

→ **Console Redirection [Disabled]**


Use **Console Redirection** option to enable or disable the console redirection function.

PPC-51xxA-H61 Panel PC

- ➔ **Disabled** **DEFAULT** Disabled the console redirection function
- ➔ **Enabled** Enabled the console redirection function

5.3.8.1 Console Redirection Settings

Use the **Console Redirection Settings** menu (**BIOS Menu 13**) to configure console redirection settings of the specified serial port. This menu appears only when the Console Redirection is enabled.

**BIOS Menu 13: Console Redirection Settings****➔ Terminal Type [ANSI]**

Use the **Terminal Type** option to specify the remote terminal type.

- ➔ **VT100** The target terminal type is VT100
- ➔ **VT100+** The target terminal type is VT100+
- ➔ **VT-UTF8** The target terminal type is VT-UTF8
- ➔ **ANSI** **DEFAULT** The target terminal type is ANSI

→ Bits per second [115200]

Use the **Bits per second** option to specify the serial port transmission speed. The speed must match the other side. Long or noisy lines may require lower speeds.

- **9600** Sets the serial port transmission speed at 9600.
- **19200** Sets the serial port transmission speed at 19200.
- **38400** Sets the serial port transmission speed at 38400.
- **57600** Sets the serial port transmission speed at 57600.
- **115200** **DEFAULT** Sets the serial port transmission speed at 115200.

→ Data Bits [8]

Use the **Data Bits** option to specify the number of data bits.

- **7** Sets the data bits at 7.
- **8** **DEFAULT** Sets the data bits at 8.

→ Parity [None]

Use the **Parity** option to specify the parity bit that can be sent with the data bits for detecting the transmission errors.

- **None** **DEFAULT** No parity bit is sent with the data bits.
- **Even** The parity bit is 0 if the number of ones in the data bits is even.
- **Odd** The parity bit is 0 if the number of ones in the data bits is odd.
- **Mark** The parity bit is always 1. This option does not provide error detection.
- **Space** The parity bit is always 0. This option does not provide error detection.

→ Stop Bits [1]

Use the **Stop Bits** option to specify the number of stop bits used to indicate the end of a serial data packet. Communication with slow devices may require more than 1 stop bit.


- ➔ 1 **DEFAULT** Sets the number of stop bits at 1.
- ➔ 2 Sets the number of stop bits at 2.

5.4 Chipset

Use the **Chipset** menu (**BIOS Menu 14**) to access the PCH and System Agent (SA) configuration menus.


**WARNING!**

Setting the wrong values for the Chipset BIOS selections in the Chipset BIOS menu may cause the system to malfunction.

**BIOS Menu 14: Chipset**

5.4.1 PCH-IO Configuration

Use the **PCH-IO Configuration** menu (**BIOS Menu 15**) to configure the PCH IO settings.



BIOS Menu 15: PCH-IO Configuration

→ **Restore AC Power Loss [Last State]**

Use the **Restore AC Power Loss** BIOS option to specify what state the system returns to if there is a sudden loss of power to the system.

- **Power Off** The system remains turned off
- **Power On** The system turns on
- **Last State** **DEFAULT** The system returns to its previous state. If it was on, it turns itself on. If it was off, it remains off.

→ **Power Saving Function(ERP) [Disabled]**

Use the **Power Saving Function(ERP)** option to enable or disable the power saving function.

PPC-51xxA-H61 Panel PC

- ➔ **Disabled** **DEFAULT** Disables the power saving function.
- ➔ **Enabled** Enables the power saving function.

5.4.1.1 PCH Azalia Configuration

Use the **PCH Azalia Configuration** menu (**BIOS Menu 16**) to configure the PCH Azalia controller.



BIOS Menu 16: PCH Azalia Configuration


➔ **Azalia [Enabled]**

The **Azalia** option enables or disables the HD Audio controller.

- ➔ **Enabled** **DEFAULT** The onboard HD Audio controller is enabled.
- ➔ **Disabled** The onboard HD Audio controller is disabled.

5.4.2 System Agent (SA) Configuration

Use the **System Agent (SA) Configuration** menu (**BIOS Menu 17**) to configure the System Agent (SA) parameters.




BIOS Menu 17: System Agent (SA) Configuration

5.4.2.1 Graphics Configuration

Use the **Graphics Configuration** menu (**BIOS Menu 18**) to configure the graphics settings

PPC-51xxA-H61 Panel PC

**BIOS Menu 18: Graphics Configuration****→ Primary Display [Auto]**

Use the **Primary Display** option to select the graphics controller used as the primary boot device.

- Auto **DEFAULT**
- IGFX
- PEG
- PCI

→ DVMT Pre-Allocated [128M]

Use the **DVMT Pre-Allocated** option to specify a fixed amount of memory that can be allocated for the internal graphics device. Configuration options are listed below.

- 128M **DEFAULT**
- 256M
- 512M


→ DVMT Total Gfx Mem [MAX]

Use the **DVMT Total Gfx Mem** option to specify the maximum amount of memory that can be allocated for the internal graphics device. Configuration options are listed below.

- 128M
- 256M
- MAX **DEFAULT**

5.4.2.1.1 LCD Control


Use the **LCD Control** menu (**BIOS Menu 19**) to display the LCD Control settings.

**BIOS Menu 19: LCD Control**

PPC-51xxA-H61 Panel PC

5.4.2.2 Memory Configuration


Use the **Memory Configuration** menu (**BIOS Menu 20**) to display the memory information.



BIOS Menu 20: Memory Configuration

5.5 Boot

Use the **Boot** menu (**BIOS Menu 21**) to configure system boot options.



BIOS Menu 21: Boot

→ Bootup NumLock State [On]

Use the **Bootup NumLock State** BIOS option to specify if the number lock setting must be modified during boot up.

- | | | |
|--------------|----------------|--|
| → On | DEFAULT | Allows the Number Lock on the keyboard to be enabled automatically when the computer system boots up. This allows the immediate use of the 10-key numeric keypad located on the right side of the keyboard. To confirm this, the Number Lock LED light on the keyboard is lit. |
| → Off | | Does not enable the keyboard Number Lock automatically. To use the 10-keys on the keyboard, press the Number Lock key located on the upper left-hand corner of the 10-key pad. The Number Lock LED on the keyboard lights up when the Number Lock is engaged. |

→ Quiet Boot [Enabled]

Use the **Quiet Boot** BIOS option to select the screen display when the system boots.

- | | |
|-------------------|--|
| → Disabled | Normal POST messages displayed |
| → Enabled | DEFAULT OEM Logo displayed instead of POST messages |

→ Option ROM Messages [Force BIOS]

Use the **Option ROM Messages** option to set the Option ROM display mode.

- | | | |
|----------------|----------------|----------------------------------|
| → Force | DEFAULT | Sets display mode to force BIOS. |
| BIOS | | |
| → Keep | | Sets display mode to current. |
| Current | | |

PPC-51xxA-H61 Panel PC


→ Launch PXE OpROM [Disabled]

Use the **Launch PXE OpROM** option to enable or disable boot option for legacy network devices.

- | | | |
|-------------------|----------------|----------------------------|
| → Disabled | DEFAULT | Ignore all PXE Option ROMs |
| → Enabled | | Load PXE Option ROMs |

5.6 Security

Use the **Security** menu (**BIOS Menu 22**) to set system and user passwords.



BIOS Menu 22: Security

→ Administrator Password


Use the **Administrator Password** to set or change an administrator password.

→ User Password

Use the **User Password** to set or change a user password.

5.7 Save & Exit

Use the **Save & Exit** menu (**BIOS Menu 23**) to load default BIOS values, optimal failsafe values and to save configuration changes.



BIOS Menu 23: Save & Exit

→ Save Changes and Reset

Use the **Save Changes and Reset** option to save the changes made to the BIOS options and reset the system.

→ Discard Changes and Reset

Use the **Discard Changes and Reset** option to exit the system without saving the changes made to the BIOS configuration setup program.

→ Restore Defaults

Use the **Restore Defaults** option to load the optimal default values for each of the parameters on the Setup menus. **F3 key can be used for this operation.**

→ Save as User Defaults

Use the **Save as User Defaults** option to save the changes done so far as user defaults.

PPC-51xxA-H61 Panel PC

→ Restore User Defaults

Use the **Restore User Defaults** option to restore the user defaults to all the setup options.

Chapter

6

Interface Connectors

6.1 Peripheral Interface Connectors

The PPC-51xxA-H61 panel PC motherboard comes with a number of peripheral interface connectors and configuration jumpers. The connector locations are shown in **Figure 6-1** and **Figure 6-2**. The Pin 1 locations of the on-board connectors are also indicated in the diagrams. The connector pinouts for these connectors are listed in the following sections.




Figure 6-1: Main Board Layout Diagram (Front Side)




Figure 6-2: Main Board Layout Diagram (Solder Side)

6.2 Internal Peripheral Connectors

Internal peripheral connectors are found on the motherboard and are only accessible when the motherboard is outside of the chassis. The table below shows a list of the peripheral interface connectors on the PPC-51xxA-H61 motherboard. Pinouts of these connectors can be found in the following sections.

Connector	Type	Label
AT/ATX switch connector	2-pin header	JATX_AT1
+12V power source connector	4-pin Molex	CPU12V1
ATX power connector	24-pin ATX	ATX1

PPC-51xxA-H61 Panel PC

Connector	Type	Label
CompactFlash® card slot (solder side)	CF slot	CF1
CMOS state setting connector	3-pin header	J_CMOS2
DIO connector	10-pin header	DIO1
Fan connector (CPU)	4-pin wafer	CPU_FAN1
Fan connector (system 1)	4-pin wafer	SYS_FAN1
Fan connector (system 2)	4-pin wafer	SYS_FAN2
Fan connector (system 3)	4-pin wafer	SYS_FAN3
Front panel connector	14-pin header	F_PANEL1
I2C connector	4-pin wafer	I2C_1
Internal audio connectors	2-pin wafer	SPKL1, SPKR1
Internal power button connector	Push button	PWR_SW1
Internal power button connector	2-pin wafer	PWR_SW2
K type thermocouple connectors	2-pin wafer	K_TYPE1, K_TYPE2
LVDS backlight connector	6-pin wafer	INVERTER1
LVDS connector	30-pin crimp	LVDS1
PCI slot	PCI slot	PCI1
PCIe x4 slot with x1 signal	PCI x4 slot	PCIE4X_1
PCIe Mini card slot (supports mSATA)	PCIe Mini card slot	MINI_PCIE1
SATA 3Gb/s connectors	SATA connector	SATA1, SATA2
SATA power connectors	2-pin wafer	JSATA_PWR1, JSATA_PWR2
SFP fiber LED connector	4-pin header	F_LED1
SMBus connector	4-pin wafer	SMBUS_1
SO-DIMM connectors	SO-DIMM connector	CHA_DIMM1, CHB_DIMM1

Connector	Type	Label
SPI Flash connector	8-pin header	JSPI1
Touch panel connector	9-pin wafer	TOUCH1
USB 2.0 connectors	8-pin header	USB1, USB2, USB3, USB4

Table 6-1: Peripheral Interface Connectors

6.2.1 +12V Power Source Connector (CPU12V1)

PIN NO.	DESCRIPTION
1	GND
2	GND
3	+12V
4	+12V

Table 6-2: +12V Power Source Connector (CPU12V1) Pinouts

6.2.2 ATX Power Connector (ATX1)

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
1	+3.3V	13	+3.3V
2	+3.3V	14	-12V
3	GND	15	GND
4	+5V	16	PS_ON-
5	GND	17	GND
6	+5V	18	GND
7	GND	19	GND
8	NC	20	NC
9	+5V	21	+5V
10	+12V	22	+5V
11	+12V	23	+5V
12	+3.3V	24	GND

Table 6-3: ATX Power Connector (ATX1) Pinouts

6.2.3 CompactFlash® Card Slot (CF1)

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
1	GROUND	26	S_IDE_Detect
2	S_D3	27	S_D11
3	S_D4	28	S_D12
4	S_D5	29	S_D13
5	S_D6	30	S_D14
6	S_D7	31	S_D15
7	S_DCS1#	32	S_DCS3#
8	GROUND	33	GROUND
9	GROUND	34	S_IOR#
10	GROUND	35	S_IOW#
11	GROUND	36	VCC_COM
12	GROUND	37	S_INT
13	VCC_COM	38	VCC_COM
14	GROUND	39	M/S
15	GROUND	40	NC
16	GROUND	41	S_RST
17	GROUND	42	S_IORDY
18	S_DA2	43	S_DRQ
19	S_DA1	44	S_DACK#
20	S DAO	45	SIDE_LED#
21	S_D0	46	S_PCBLID
22	S_D1	47	S_D8
23	S_D2	48	S_D9
24	NC	49	S_D10
25	CFD2	50	GROUND

Table 6-4: CompactFlash® Card Slot (CF1) Pinouts

6.2.4 DIO Connector (DIO1)

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION	
1	GND	2	VCC	
3	Output 3	4	Output 2	
5	Output 1	6	Output 0	
7	Input 3	8	Input 2	
9	Input 1	10	Input 0	




Table 6-5: DIO Connector (DIO1) Pinouts

6.2.5 Fan Connector (CPU_FAN1/SYS_FAN1/SYS_FAN2/SYS_FAN3)

PIN NO.	DESCRIPTION
1	GND
2	+12V
3	SENSE
4	CONTROL

Table 6-6: Fan Connector Pinouts

6.2.6 I2C Connector (I2C_1)

PIN NO.	DESCRIPTION
1	+5V_DUAL
2	PCH_GP38_PU
3	PCH_GP39_PU
4	GND

Table 6-7: Fan Connector (I2C_1) Pinouts

6.2.7 Internal Audio Connector (SPKL1)

PIN NO.	DESCRIPTION
1	LOUT-
2	LOUT +

Table 6-8: Internal Audio Connector (SPKL1) Pinouts

6.2.8 Internal Audio Connector (SPKR1)

PIN NO.	DESCRIPTION
1	ROUT-
2	ROUT +

Table 6-9: Internal Audio Connector (SPKR1) Pinouts

6.2.9 Internal Power Button Connector (PWR_SW1)

PIN NO.	DESCRIPTION
1	PWRBTN_SW#_C
2	PWRBTN_SW#_C
3	GND
4	GND

Table 6-10: Internal Power Button Connector (PWR_SW1) Pinouts

6.2.10 Internal Power Button Connector (PWR_SW2)

PIN NO.	DESCRIPTION
1	PWRBTN_SW#_C
2	GND

Table 6-11: Internal Power Button Connector (PWR_SW2) Pinouts

6.2.11 K Type Thermocouple Connectors (K_TYPE1/K_TYPE2)

PIN NO.	DESCRIPTION
1	D-
2	D+

**Table 6-12: K Type Thermocouple Connectors (K_TYPE1/K_TYPE2)
Pinouts**

6.2.12 LVDS Backlight Connector (INVERTER1)

PIN NO.	DESCRIPTION
1	+12V
2	+12V
3	Backlight ON/OFF
4	Backlight Brightness Control
5	GND
6	GND

Table 6-13: LVDS Backlight Connector (INVERTER1) Pinouts

6.2.13 LVDS Connector (LVDS1)

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
1	GND	2	GND
3	LVDSA0+	4	LVDSA0-
5	LVDSA1+	6	LVDSA1-
7	LVDSA2+	8	LVDSA2-
9	LVDSACLK+	10	LVDSACLK-
11	LVDSA3+	12	N LVDSA3-
13	GND	14	GND
15	LVDSA4+	16	LVDSA4-
17	LVDSA5+	18	LVDSA5-
19	LVDSA6+	20	LVDSA6-
21	LVDSBCLK+	22	LVDSBCLK-

PPC-51xxA-H61 Panel PC

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
23	LVDSA7+	24	LVDSA7-
25	GND	26	GND
27	LCDVCC	28	LCDVCC
29	LCDVCC	30	LCDVCC

Table 6-14: LVDS Connector (LVDS1) Pinouts**6.2.14 PCIe Mini Card Slot (MINI_PCIE1)**

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
1	WAKE#	2	3.3 V
3	RESERVED	4	GND
5	RESERVED	6	1.5 V
7	CLKREQ#	8	N/C
9	GND	10	N/C
11	REFCLK-	12	N/C
13	REFCLK+	14	N/C
15	GND	16	N/C
17	N/C	18	GND
19	N/C	20	W_DISABLE#
21	GND	22	PERST#
23	PERn0	24	3.3VAUX
25	PERp0	26	GND
27	GND	28	1.5 V
29	GND	30	SMBCLK
31	PETn0	32	SMBDATA
33	PETp0	34	GND
35	GND	36	USBD-
37	RESERVED	38	USBD+
39	RESERVED	40	GND
41	RESERVED	42	LED_WWAN#
43	RESERVED	44	LED_WLAN#
45	RESERVED	46	LED_WPAN#

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
47	RESERVED	48	1.5 V
49	RESERVED	50	GND
51	RESERVED	52	3.3 V

Table 6-15: PCIe Mini Card Slot (MINI_PCIE1) Pinouts

6.2.15 SATA 3Gb/s Connectors (SATA1/SATA2)

PIN NO.	DESCRIPTION
1	GND
2	SATATXP
3	SATATXN
4	GND
5	SATARXN
6	SATARXP
7	GND

Table 6-16: SATA 3Gb/s Connectors (SATA1/SATA2) Pinouts

6.2.16 SATA Power Connectors (JSATA_PWR1/JSATA_PWR2)

PIN NO.	DESCRIPTION
1	+5V
2	GND

Table 6-17: SATA Power Connectors (JSATA_PWR1/JSATA_PWR2) Pinouts

6.2.17 SFP Fiber LED Connector (F_LED1)

PIN NO.	DESCRIPTION
1	FIBER0_LED-
2	FIBER0_LED+
3	FIBER1_LED-
4	FIBER1_LED+

Table 6-18: SATA Power Connectors (JSATA_PWR1/JSATA_PWR2 Pinouts

6.2.18 SMBus Connector (SMBUS_1)

PIN NO.	DESCRIPTION
1	+5V_DUAL
2	SMBCLK
3	SMBDATA
4	GND

Table 6-19: SMBus Connector (SMBUS_1) Pinouts

6.2.19 SPI Flash Connector (JSPI1)

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION	
1	SPI_VCC	2	GND	1 2
3	SPI_CS0	4	SPI_CLK0	7 8
5	SPI_SO0	6	SPI_SIO	
7	NC	8	NC	

Table 6-20: SPI Flash Connector (JSPI1) Pinouts

6.2.20 Touch Panel Connector (TOUCH1)

PIN NO.	8-Wire	4-Wire	5-Wire
1	Right Sense	N/A	N/A
2	Left Sense	N/A	N/A
3	Bottom Sense	N/A	N/A
4	Top Sense	N/A	Sense (S)
5	Right Excite	Right	LR (X)
6	Left Excite	Left	LL (L)
7	Bottom Excite	Bottom	UR (Y)
8	Top Excite	Top	UL (Y)
9	GND	GND	GND

Table 6-21: Touch Panel Connector (TOUCH1) Pinouts

6.2.21 USB 2.0 Connectors (USB1/USB2/USB3/USB4)


PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION	
1	VCC	2	GND	
3	DATA-	4	DATA+	
5	DATA+	6	DATA-	
7	GND	8	VCC	

Table 6-22: USB 2.0 Connector (USB1/USB2/USB3/USB4) Pinouts

6.3 External Interface Panel Connectors

The table below lists the rear panel connectors on the PPC-51xxA-H61 motherboard.

Pinouts of these connectors can be found in the following sections.

Connector	Type	Label
Audio connector (line-out and mic-in)	Audio jack	AUDIO1
RJ-45 LAN connectors	RJ-45	LAN1/2
Reset button	Push button	RST_SW1

PPC-51xxA-H61 Panel PC

Connector	Type	Label
RS-232 serial ports	DB-9	COM1/2, COM3/4
SFP fiber LAN connectors	SFP fiber	FIBER1
USB 2.0 connectors	USB 2.0 port	USB_CON2
USB 3.0 connectors	USB 3.0 port	USB_CON1
VGA and RS-232/422/485 serial port connector	15-pin female, DB-9	COM5_VGA1

Table 6-23: Rear Panel Connectors**6.3.1 RJ-45 LAN Connector (LAN1/2)**

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
1	MDIA3-	2	MDIA3+
3	MDIA1-	4	MDIA2-
5	MDIA2 +	6	MDIA1 +
7	MDIA0-	8	MDIA0 +

Table 6-24: RJ-45 LAN Connector Pinouts**6.3.2 RS-232 Serial Ports (COM1/2, COM3/4)**

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
1	DCD	2	RXD
3	TXD	4	DTR
5	GND	6	DSR
7	RTS	8	CTS
9	RI		

Table 6-25: RS-232 Serial Port Pinouts

6.3.3 RS-232/422/485 Serial Port (COM5)

PIN NO.	RS-232	RS-422	RS-485
1	-NDCD	TXD422#	TXD485#
2	NSIN	TXD422+	TXD485+
3	NSOUT	RXD422+	
4	-NDTR	RXD422#	
5	GND		
6	-NDSR		
7	-NRTS		
8	-NCTS		
9	COMPIN9		

Table 6-26: RS-232/422/485 Serial Port Pinouts

6.3.4 USB 2.0 Connectors (USB_CON2)

PIN NO.	DESCRIPTION
1	VCC
2	DATA-
3	DATA+
4	GND

Table 6-27: USB 2.0 Connectors (USB_CON2) Pinouts

6.3.5 USB 3.0 Connectors (USB_CON1)

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
1	USB3_PWR1	10	USB3_PWR2
2	USB2PO_DM1	11	USB2PO_DM2
3	USB2PO_DP1	12	USB2PO_DP2
4	GND	13	GND
5	USB3PO_RXDN1	14	USB3PO_RXDN2
6	USB3PO_RXDP1	15	USB3PO_RXDP2
7	GND	16	GND

PPC-51xxA-H61 Panel PC

8	USB3PO_TXDN1	17	USB3PO_TXDN2
9	USB3PO_TXDP1	18	USB3PO_TXDP2

Table 6-28: USB 3.0 Connectors (USB_CON1) Pinouts**6.3.6 VGA Connector (VGA1)**

PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION
1	RED	9	5V
2	GREEN	10	GROUND
3	BLUE	11	NC
4	NC	12	DDCDAT
5	GROUND	13	H SYNC
6	GROUND	14	V SYNC
7	GROUND	15	DDCCLK
8	GROUND		

Table 6-29: VGA Connector (VGA1) Pinouts**6.4 Preconfigured Jumper Settings**

The following jumpers are preconfigured for the PPC-51xxA-H61. Users should not change these jumpers (**Table 6-30**). It is only for reference.

Jumper Name	Label	Type
CF card power selection	JP1	3-pin header
CPU fan type selection	JCPUFAN1	3-pin header
Inverter brightness voltage selection	J_ADJ1	3-pin header
LCD power selection	JLCD_PWR1	6-pin header
Panel type and resolution selection	JLCD_SET1	8-pin header
Pull high/low selection (for RS-422/485 only)	UART_SEL1	8-pin header

System fan type selection	JSYSFAN1, JSYSFAN3	3-pin header
Touchscreen selection	JTOUCH1	4-pin header
USB1 ~ USB4 power selection	USBAB_PWR1, USB01_PWR1, USB23_PWR1, USB45_PWR1	3-pin header

Table 6-30: Preconfigured Jumpers

6.4.1 CF Card Power Selection Jumper (JP1)

Pin	Description
Short 1-2	+5 V (Default)
Short 2-3	+3.3 V

Table 6-31: CF Card Power Selection Jumper (JP1) Settings

6.4.2 CPU Fan Type Selection Jumper (JCPUFAN1)

Pin	Description
Open	4-pin Fan (Default)
Short 2-3	3-pin Fan

Table 6-32: CPU Fan Type Selection Jumper (JCPUFAN1) Settings

6.4.3 Inverter Brightness Voltage Selection Jumper (J_ADJ1)

Pin	Description
Short 1-2	+5 V (Default)
Short 2-3	+3.3 V

Table 6-33: Inverter Brightness Voltage Selection Jumper (J_ADJ1) Settings

PPC-51xxA-H61 Panel PC

6.4.4 LCD Power Selection Jumper (JLCD_PWR1)

Pin	Description
Short 1-2	+3.3V (Default)
Short 3-4	+5 V
Short 5-6	+12 V

Table 6-34: LCD Power Selection Jumper (JLCD_PWR1) Settings**6.4.5 Panel Type and Resolution Selection Jumper (JLCD_SET1)**

Resolution	Pin 3-4	Pin 1-2
1280x1024, 48 bits	Short	Short
1280x1024, 36 bits	Short	Open
1024x768, 18 bits	Open	Short
1024x768, 24 bits	Open	Open

Panel Type	Pin 7-8	Pin 5-6
CRT+LCD	Short	Short
LCD	Short	Open
CRT	Open	Short
AUTO	Open	Open

Table 6-35: Panel Type and Resolution Selection Jumper (JLCD_SET1) Settings**6.4.6 Pull High/Low Selection (for RS-422/485 only) Jumper (UART_SEL1)**

Pin	Description
Short 1-2	2.2K Pull Low
Short 3-4	2.2K Pull High
Short 5-6	2.2K Pull High
Short 7-8	2.2K Pull Low

Table 6-36: Pull High/Low Selection (for RS-422/485 only) Jumper (UART_SEL1) Settings

6.4.7 System Fan Type Selection Jumper (JSYSFAN1/JSYSFAN3)

Pin	Description
Open	4-pin Fan (Default)
Short 2-3	3-pin Fan

Table 6-37: System Fan Type Selection Jumper Settings

6.4.8 Touchscreen Selection Jumper (JTOUCH1)

Type	Pin 1-2	Pin 3-4
5-Wire (Default)	Short	Open
4-Wire and 8-Wire	Open	Short

Table 6-38: Touchscreen Selection Jumper (JTOUCH1) Settings

6.4.9 USB1~USB4 Power Selection Jumpers

Pin	Description
Short 1-2	+5V_DUAL
Short 2-3	+5V (Default)

Table 6-39: USB1~USB4 Power Selection Jumpers Settings

Appendix

A

Regulatory Compliance

DECLARATION OF CONFORMITY

This equipment is in conformity with the following EU directives:

- EMC Directive 2004/108/EC
- Low-Voltage Directive 2006/95/EC
- RoHS II Directive 2011/65/EU
- Ecodesign Directive 2009/125/EC

If the user modifies and/or install other devices in the equipment, the CE conformity declaration may no longer apply.

If this equipment has telecommunications functionality, it also complies with the requirements of the R&TTE Directive 1999/5/EC.

English

IEI Integration Corp declares that this equipment is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.

Български [Bulgarian]

IEI Integration Corp. декларира, че този оборудване е в съответствие със съществените изисквания и другите приложими правила на Директива 1999/5/EC.

Česky [Czech]

IEI Integration Corp tímto prohlašuje, že tento zařízení je ve shodě se základními požadavky a dalšími příslušnými ustanoveními směrnice 1999/5/ES.

Dansk [Danish]

IEI Integration Corp erklærer herved, at følgende udstyr overholder de væsentlige krav og øvrige relevante krav i direktiv 1999/5/EF.

Deutsch [German]

IEI Integration Corp, erklärt dieses Gerät entspricht den grundlegenden Anforderungen und den weiteren entsprechenden Vorgaben der Richtlinie 1999/5/EU.

Eesti [Estonian]

IEI Integration Corp deklareerib seadme seadme vastavust direktiivi 1999/5/EÜ põhinõuetele ja nimetatud direktiivist tulenevatele teistele asjakohastele sätetele.

PPC-51xxA-H61 Panel PC

Español [Spanish]

IEI Integration Corp declara que el equipo cumple con los requisitos esenciales y cualesquiera otras disposiciones aplicables o exigibles de la Directiva 1999/5/CE.

Ελληνική [Greek]

ΙΕΙ Integration Corp ΔΗΛΩΝΕΙ ΟΤΙ ΕΞΟΠΛΙΣΜΟΣ ΣΥΜΜΟΡΦΩΝΕΤΑΙ ΠΡΟΣ ΤΙΣ ΟΥΣΙΩΔΕΙΣ ΑΠΑΙΤΗΣΕΙΣ ΚΑΙ ΤΙΣ ΛΟΙΠΕΣ ΣΧΕΤΙΚΕΣ ΔΙΑΤΑΞΕΙΣ ΤΗΣ ΟΔΗΓΙΑΣ 1999/5/EK.

Français [French]

IEI Integration Corp déclare que l'appareil est conforme aux exigences essentielles et aux autres dispositions pertinentes de la directive 1999/5/CE.

Italiano [Italian]

IEI Integration Corp dichiara che questo apparecchio è conforme ai requisiti essenziali ed alle altre disposizioni pertinenti stabilite dalla direttiva 1999/5/CE.

Latviski [Latvian]

IEI Integration Corp deklarē, ka iekārta atbilst būtiskajām prasībām un citiem ar to saistītajiem noteikumiem Direktīvas 1999/5/EK.

Lietuvių [Lithuanian]

IEI Integration Corp deklaruoją, kad šis įranga atitinka esminius reikalavimus ir kitas 1999/5/EB Direktyvos nuostatas.

Nederlands [Dutch]

IEI Integration Corp dat het toestel toestel in overeenstemming is met de essentiële eisen en de andere relevante bepalingen van richtlijn 1999/5/EG.

Malti [Maltese]

IEI Integration Corp jiddikjara li dan prodott jikkonforma mal-ħtiġijiet essenziali u ma provvedimenti oħrajn relevanti li hemm fid-Dirrettiva 1999/5/EC.

Magyar [Hungarian]

IEI Integration Corp nyilatkozom, hogy a berendezés megfelel a vonatkozó alapvető követelményeknek és az 1999/5/EC irányelv egyéb előírásainak.

Polski [Polish]

IEI Integration Corp oświadcza, że wyrobu jest zgodny z zasadniczymi wymogami oraz pozostałymi stosownymi postanowieniami Dyrektywy 1999/5/EC.

Português [Portuguese]

IEI Integration Corp declara que este equipamento está conforme com os requisitos essenciais e outras disposições da Directiva 1999/5/CE.

Româna [Romanian]

IEI Integration Corp declară că acest echipament este în conformitate cu cerințele esențiale și cu celelalte prevederi relevante ale Directivei 1999/5/CE.

Slovensko [Slovenian]

IEI Integration Corp izjavlja, da je ta opreme v skladu z bistvenimi zahtevami in ostalimi relevantnimi določili direktive 1999/5/ES.

Slovensky [Slovak]

IEI Integration Corp týmto vyhlasuje, že zariadenia spĺňa základné požiadavky a všetky príslušné ustanovenia Smernice 1999/5/ES.

Suomi [Finnish]

IEI Integration Corp vakuuttaa täten että laitteet on direktiivin 1999/5/EY oleellisten vaatimusten ja sitä koskevien direktiivin muiden ehtojen mukainen.

Svenska [Swedish]

IEI Integration Corp förklarar att denna utrustningstyp står i överensstämmelse med de väsentliga egenskapskrav och övriga relevanta bestämmelser som framgår av direktiv 1999/5/EG.

**FCC WARNING**

This equipment complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference, and
- This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Appendix

B

BIOS Configuration Options

B.1 BIOS Configuration Options

Below is a list of BIOS configuration options described in Chapter 5.

BIOS Information	74
System Date [xx/xx/xx]	75
System Time [xx:xx:xx]	75
ACPI Sleep State [S1 only (CPU Stop Clock)].....	76
Wake system with Fixed Time [Disabled].....	77
Intel Virtualization Technology [Disabled]	79
SATA Controller(s) [Enabled]	80
SATA Mode Selection [IDE]	80
USB Devices.....	81
Legacy USB Support [Enabled].....	81
Serial Port [Enabled].....	83
Change Settings [Auto]	83
Serial Port [Enabled].....	84
Change Settings [Auto]	84
Serial Port [Enabled].....	85
Change Settings [Auto]	85
Serial Port [Enabled].....	86
Change Settings [Auto]	86
Serial Port [Enabled].....	86
Device Mode [Normal]	87
Change Settings [Auto]	87
PC Health Status	88
CPU_FAN1/SYS_FAN2/SYS_FAN3 Smart Fan Control [Auto by RPM]	89
CPU Temperature n/System Temperature n/Temperature n	90
Duty Cycle n	90
Console Redirection [Disabled]	90
Terminal Type [ANSI].....	91
Bits per second [115200].....	92
Data Bits [8]	92
Parity [None].....	92
Stop Bits [1]	93

Restore AC Power Loss [Last State]	94
Power Saving Function(ERP) [Disabled].....	94
Azalia [Enabled]	95
Primary Display [Auto]	97
DVMT Pre-Allocated [128M]	97
DVMT Total Gfx Mem [MAX].....	98
Bootup NumLock State [On].....	100
Quiet Boot [Enabled]	100
Option ROM Messages [Force BIOS].....	100
Launch PXE OpROM [Disabled].....	101
Administrator Password	101
User Password	101
Save Changes and Reset	102
Discard Changes and Reset	102
Restore Defaults	102
Save as User Defaults	102
Restore User Defaults	103

Appendix

C

Safety Precautions

**WARNING:**

The precautions outlined in this chapter should be strictly followed. Failure to follow these precautions may result in permanent damage to the EP series.

C.1 Safety Precautions

Please follow the safety precautions outlined in the sections that follow:

C.1.1 General Safety Precautions

Please ensure the following safety precautions are adhered to at all times.

- **Follow the electrostatic precautions** outlined below whenever the EP series is opened.
- **Make sure the power is turned off and the power cord is disconnected** whenever the EP series is being installed, moved or modified.
- **Do not apply voltage levels that exceed the specified voltage range.** Doing so may cause fire and/or an electrical shock.
- **Electric shocks can occur** if the EP series chassis is opened when the EP series is running.
- **Do not drop or insert any objects** into the ventilation openings of the EP series.
- **If considerable amounts of dust, water, or fluids enter the EP series**, turn off the power supply immediately, unplug the power cord, and contact the EP series vendor.
- **DO NOT:**
 - Drop the EP series against a hard surface.
 - Strike or exert excessive force onto the LCD panel.
 - Touch any of the LCD panels with a sharp object
 - In a site where the ambient temperature exceeds the rated temperature

C.1.2 Anti-static Precautions



WARNING:

Failure to take ESD precautions during the installation of the EP series may result in permanent damage to the EP series and severe injury to the user.

Electrostatic discharge (ESD) can cause serious damage to electronic components, including the EP series. Dry climates are especially susceptible to ESD. It is therefore critical that whenever the EP series is opened and any of the electrical components are handled, the following anti-static precautions are strictly adhered to.

- ***Wear an anti-static wristband:*** Wearing a simple anti-static wristband can help to prevent ESD from damaging any electrical component.
- ***Self-grounding:*** Before handling any electrical component, touch any grounded conducting material. During the time the electrical component is handled, frequently touch any conducting materials that are connected to the ground.
- ***Use an anti-static pad:*** When configuring or working with an electrical component, place it on an anti-static pad. This reduces the possibility of ESD damage.
- ***Only handle the edges of the electrical component:*** When handling the electrical component, hold the electrical component by its edges.

C.1.3 Product Disposal



CAUTION:

Risk of explosion if battery is replaced by an incorrect type. Only certified engineers should replace the on-board battery.

Dispose of used batteries according to instructions and local regulations.

- Outside the European Union - If you wish to dispose of used electrical and electronic products outside the European Union, please contact your local authority so as to comply with the correct disposal method.
- Within the European Union:



EU-wide legislation, as implemented in each Member State, requires that waste electrical and electronic products carrying the mark (left) must be disposed of separately from normal household waste. This includes monitors and electrical accessories, such as signal cables or power cords. When you need to dispose of your display products, please follow the guidance of your local authority, or ask the shop where you purchased the product. The mark on electrical and electronic products only applies to the current European Union Member States.

Please follow the national guidelines for electrical and electronic product disposal.

C.2 Maintenance and Cleaning Precautions

When maintaining or cleaning the EP series, please follow the guidelines below.

C.2.1 Maintenance and Cleaning

Prior to cleaning any part or component of the EP series, please read the details below.

- Except for the LCD panel, never spray or squirt liquids directly onto any other components. To clean the LCD panel, gently wipe it with a piece of soft dry cloth or a slightly moistened cloth.
- The interior of the EP series does not require cleaning. Keep fluids away from the EP series interior.
- Be cautious of all small removable components when vacuuming the EP series.
- Turn the EP series off before cleaning the EP series.
- Never drop any objects or liquids through the openings of the EP series.
- Be cautious of any possible allergic reactions to solvents or chemicals used when cleaning the EP series.
- Avoid eating, drinking and smoking within vicinity of the EP series.

C.2.2 Cleaning Tools

Some components in the EP series may only be cleaned using a product specifically designed for the purpose. In such case, the product will be explicitly mentioned in the cleaning tips. Below is a list of items to use when cleaning the EP series.

- **Cloth** – Although paper towels or tissues can be used, a soft, clean piece of cloth is recommended when cleaning the EP series.
- **Water or rubbing alcohol** – A cloth moistened with water or rubbing alcohol can be used to clean the EP series.
- **Using solvents** – The use of solvents is not recommended when cleaning the EP series as they may damage the plastic parts.
- **Vacuum cleaner** – Using a vacuum specifically designed for computers is one of the best methods of cleaning the EP series. Dust and dirt can restrict the airflow in the EP series and cause its circuitry to corrode.
- **Cotton swabs** - Cotton swaps moistened with rubbing alcohol or water are excellent tools for wiping hard to reach areas.
- **Foam swabs** - Whenever possible, it is best to use lint free swabs such as foam swabs for cleaning.

Appendix

D

Watchdog Timer

**NOTE:**

The following discussion applies to DOS environment. IEI support is contacted or the IEI website visited for specific drivers for more sophisticated operating systems, e.g., Windows and Linux.

The Watchdog Timer is provided to ensure that standalone systems can always recover from catastrophic conditions that cause the CPU to crash. This condition may have occurred by external EMI or a software bug. When the CPU stops working correctly, Watchdog Timer either performs a hardware reset (cold boot) or a Non-Maskable Interrupt (NMI) to bring the system back to a known state.

A BIOS function call (INT 15H) is used to control the Watchdog Timer:

INT 15H:

AH – 6FH Sub-function:	
AL – 2:	Sets the Watchdog Timer's period.
BL:	Time-out value (Its unit-second is dependent on the item "Watchdog Timer unit select" in CMOS setup).

Table D-1: AH-6FH Sub-function

Call sub-function 2 to set the time-out period of Watchdog Timer first. If the time-out value is not zero, the Watchdog Timer starts counting down. While the timer value reaches zero, the system resets. To ensure that this reset condition does not occur, calling sub-function 2 must periodically refresh the Watchdog Timer. However, the Watchdog timer is disabled if the time-out value is set to zero.

A tolerance of at least 10% must be maintained to avoid unknown routines within the operating system (DOS), such as disk I/O that can be very time-consuming.

**NOTE:**

When exiting a program it is necessary to disable the Watchdog Timer,
otherwise the system resets.

Example program:

```
; INITIAL TIMER PERIOD COUNTER
;
W_LOOP:
    MOV     AX, 6F02H      ;setting the time-out value
    MOV     BX, 05          ;time-out value is 5 seconds
    INT     15H
;
; ADD THE APPLICATION PROGRAM HERE
;
    CMP     EXIT_AP, 1      ;is the application over?
    JNE     W_LOOP          ;No, restart the application
;
    MOV     AX, 6F02H      ;disable Watchdog Timer
    MOV     BX, 0            ;
    INT     15H
;
; EXIT :
```

Appendix

E

Hazardous Materials Disclosure

E.1 Hazardous Material Disclosure Table for IPB Products Certified as RoHS Compliant Under 2002/95/EC Without Mercury

The details provided in this appendix are to ensure that the product is compliant with the Peoples Republic of China (China) RoHS standards. The table below acknowledges the presences of small quantities of certain materials in the product, and is applicable to China RoHS only.

A label will be placed on each product to indicate the estimated “Environmentally Friendly Use Period” (EFUP). This is an estimate of the number of years that these substances would “not leak out or undergo abrupt change.” This product may contain replaceable sub-assemblies/components which have a shorter EFUP such as batteries and lamps. These components will be separately marked.

Please refer to the table on the next page.

PPC-51xxA-H61 Panel PC

Part Name	Toxic or Hazardous Substances and Elements					
	Lead (Pb)	Mercury (Hg)	Cadmium (Cd)	Hexavalent Chromium (CR(VI))	Polybrominated Biphenyls (PBB)	Polybrominated Diphenyl Ethers (PBDE)
Housing	O	O	O	O	O	O
Display	O	O	O	O	O	O
Printed Circuit Board	O	O	O	O	O	O
Metal Fasteners	O	O	O	O	O	O
Cable Assembly	O	O	O	O	O	O
Fan Assembly	O	O	O	O	O	O
Power Supply Assemblies	O	O	O	O	O	O
Battery	O	O	O	O	O	O

O: This toxic or hazardous substance is contained in all of the homogeneous materials for the part is below the limit requirement in SJ/T11363-2006

X: This toxic or hazardous substance is contained in at least one of the homogeneous materials for this part is above the limit requirement in SJ/T11363-2006

此附件旨在确保本产品符合中国 RoHS 标准。以下表格标示此产品中某有毒物质的含量符合中国 RoHS 标准规定的限量要求。

本产品上会附有“环境友好使用期限”的标签，此期限是估算这些物质“不会有泄漏或突变”的年限。本产品可能包含有较短的环境友好使用期限的可替换元件，像是电池或灯管，这些元件将会单独标示出来。

部件名称	有毒有害物质或元素					
	铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)
壳体	O	O	O	O	O	O
显示	O	O	O	O	O	O
印刷电路板	O	O	O	O	O	O
金属螺帽	O	O	O	O	O	O
电缆组装	O	O	O	O	O	O
风扇组装	O	O	O	O	O	O
电力供应组装	O	O	O	O	O	O
电池	O	O	O	O	O	O

O: 表示该有毒有害物质在该部件所有物质材料中的含量均在 SJ/T11363-2006 标准规定的限量要求以下。

X: 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出 SJ/T11363-2006 标准规定的限量要求。