

JN 3018G **V.S** Advanced JN 3018G



JetNet 3018G

NEW



Advanced JetNet 3018G

Interface

10/100TX Ports

16

16

10/100/1000TX Ports

100/1000TX Combo x2

100/1000TX Combo x2

Fiber Ports

Gigabit SFP Combo x2

100/1000FX SFP Combo x2

DI/DO (Dry Relay)

DO x2

DO x2

Power Input

DC24V x2 (12~48V)

DC24V x2 (10~60V)

Hi-Pot

AC 1.5KV

AC 1.5KV

Performance

MAC Address

8K

8K

Packet Buffer

2Mbits

3Mbits

Jumbo Frame

9.2Kbytes

2Kbytes

QoS Traffic Priority

4 Queues

4 Queues

Broadcast Storm filter

-

Yes, default disable

Port/Power Event Alarm

Port 17, 18 Alarm

Power Alarm (DO1)

Port 17, 18 Alarm (DO2)

HW/ME

Housing Protection (IP)

IP31 Aluminum

IP31 Aluminum

Dimesnion (HxWxD mm)

137 x 96 x 129

137 x 96 x 129

Mounting

Din-rail/Wall mount

Din-rail/Wall mount

Operating Temperature

-25~70°C

-40~75°C

Certification

Regulatory/Approval

CE/FCC/UL508

CE/FCC/EN50121-4 (Compliance)