

PAC-125G

10-slot Full-size Compact Chassis






CD-ROM and HDD are not included in package



Features

- RoHS compliant design
- Two USB ports on the front panel
- One 80mm x 80mm x 25mm hot swappable cooling fan with fan filter
- 2 x 5.25", 1 x 3.5" HDD, 1 x front-accessible 3.5" drive bays
- Lockable door prevents unauthorized access

Dimensions *(Unit: mm)*



Specifications

◆ **Construction**	Heavy duty metal
◆ **SBC Form Factor**	Full-size, slot CPU card
◆ **Drive Bays**	2 x 5.25"
	1 x Front accessible 3.5"
	1 x 3.5" HDD
◆ **Cooling Fans**	80mm x 80mm x 25mm
◆ **I/O Ports**	2 x USB
◆ **I/O Openings**	1 x LPT, 1 x COM
◆ **Expansion Slots**	10 slots
◆ **Indicators**	Power, HDD
◆ **Buttons**	Power switch, reset
◆ **Operating Temperature**	0°C ~ 50°C
◆ **Operating Humidity**	10% ~ 90%
◆ **Color**	W: White
◆ **Weight (Net/Gross)**	7.2 kg/10.4 kg
◆ **Dimensions (DxWxH)**	420 mm x 321 mm x 176 mm

Backplane Options

Model No.	SBC Type	PCI	ISA	PCIX	PCIe				PSU Connector
					x1	x4	x8	x16	
BP-10S-RS	ISA	0	10	0	0	0	0	0	AT
PCI-10S-RS	PICMG 1.0	4	5	0	0	0	0	0	AT/ATX
PX-10S-RS	PICMG 1.0	7	3	0	0	0	0	0	AT/ATX
IP-8S-RS	PCISA	4	3	0	0	0	0	0	AT/ATX
IP-10S-RS	PCISA	4	5	0	0	0	0	0	AT/ATX
IPX-9S-RS	PCISA	8	0	0	0	0	0	0	AT/ATX
HPE-8S	PCI/PICOe	4	0	0	2	0	0	0	ATX
PE-6S	PICMG 1.3	2	0	0	2	0	0	1	ATX
PE-8S*	PICMG 1.3	3	0	0	3	0	0	1	ATX
SPXE-9S	PICMG 1.3	2	0	2	0	2	1	0	ATX
SPE-9S	PICMG 1.3	3	0	0	0	3	1	0	ATX

*Only R20 or later versions support PICMG 1.3 backplane

Ordering Information

Part No.	Description
PAC-125GW-R22/A130B	10-slot full-size compact chassis, white, 1 x 8cm fan, with ACE-A130B-R10 (300W ATX model), RoHS

Power Supply Options

Type	Model No.	Watt
AT	ACE-925AP-U-RS	250W
	ACE-935AL-RS	300W
ATX	ACE-A130B-R10	300W
	ACE-A140A-S-R11	400W
	ACE-A160A-R11	600W

PAC-125G supports single PS/2 PSU. For more IEI PSU models, please refer to section 5 or visit www.ieiworld.com.