



TRIMBLE GPS ANTENNAS

GPS ANTENNAS FOR EMBEDDED SYSTEMS

BENEFIT HIGHLIGHTS

- Active GPS antennas include low noise amplifier
- Three form factors: Magnetic Mount, Unpackaged, and Bulkhead
- Various connector options
- 3 V or 5 V supply voltage
- Ideal for complete solutions

KEY FEATURES

- Magnetic Mount, Unpackaged, and Bulkhead micropatch active GPS antennas
- Internal low noise amplifier (LNA)
- Waterproof, corrosion-resistant (packaged versions only)
- Mounting / Connector choices:
 - Magnetic mount: MCX, SMA, SMB connectors
 - Unpackaged: H.FL right-angle connector
 - Bulkhead: TNC connector
- Specifications:
 - Frequency range: 1,575.42 MHz
 - Gain: up to 28 dBi @ 25 °C
 - Output Impedance: 50 Ω
 - LNA Noise Figure: as low as 1.5 dB @ 25 °C

YOUR CHOICE OF GPS ANTENNAS

Trimble offers a variety of active micropatch antenna products for use with Trimble's GPS receivers to suit many applications.

All packaged antennas are waterproof and corrosion resistant. All antennas include an internal low noise amplifier (LNA) to provide sensitive performance in the toughest environments (-40 °C to +85 °C with high humidity).

Trimble's antenna products are built with the best components and meet the highest production quality standards.

Are you designing a system with a Trimble GPS receiver? Are you looking for top-tier positioning performance, accuracy, and sensitivity? These antennas complete your GPS solution from Trimble.

FORM FACTORS OF YOUR CHOICE

Trimble GPS antennas are available in several form factors, providing choices of housing, mounting and connectors, as well as choice of supply voltage (3 V or 5 V).

Magnetic Mount antennas, with their small size and slim profile, are designed for quick and convenient installation on, or inside, vehicles or equipment. The tough plastic housing and magnetic base enable them to withstand exposure to shock, vibration, and weather extremes. Available in both 3 V and 5 V models, they additionally provide a choice of connector type.

The 3 V **Unpackaged** antenna is embeddable within devices and systems. It has the lowest power consumption (5 to 13 mA), an H.FL right-angle connector, and an 85 mm cable.

Bulkhead models, in both 3 V and 5 V, are designed for drill-through mounting on vehicle roof and trunk panels. The tough plastic housing and the feedthrough threaded nut mount enable these units to withstand exposure to shock, vibration, and weather extremes. These models feature a TNC connector.

SUPPLY VOLTAGES TO SUIT RECEIVERS

The 5 V antennas are designed for use with Trimble's Lassen SK II GPS receiver and with receivers from other manufacturers.

The 3 V antennas, which are ideal for GPS devices requiring lower power consumption, are designed for use with receivers from other manufacturers and with the following GPS receiver modules from Trimble:

- Condor
- Copernicus
- Lassen iQ
- Lassen LP
- Lassen SQ
- Silvana



TRIMBLE GPS ANTENNAS

GPS ANTENNAS FOR EMBEDDED SYSTEMS

MODEL COMPARISON

Differentiating Features and Key Specifications.¹

MODEL TYPE	MOUNT	DIMENSIONS	WEIGHT	CABLE LENGTH	SUPPLY VOLTAGE	POWER CONSUMPTION	OUTPUT CONNECTOR	CABLE TYPE	PART NUMBER
Magnetic Mount 66800-XX	Magnetic	37.4 mm x 34 mm x 12.9 mm	25 g (without cable)	5 m	5 V	30 mA max	SMB ²	RG-174	66800-00
					3 V	20 mA max 15 mA typ	SMA ²	RG-174	66800-50
							SMA ²	RG-174	66800-52
Unpackaged 66801-XX	Embedded	22 mm x 21 mm x 7.5 mm	20 g	85 mm	3 V	5 mA to 13 mA	H.FL ³	RF-MF507	66801-00
Bulkhead 70228-XX	Threaded Nut Mount	64.5 mm dia x 40 mm	150 g	N/A	5 V	35 mA max	TNC	N/A	70228-70
					3 V	35 mA max	TNC	N/A	70228-00

1. Standard models; special order models are available.

2. Straight plug.

3. Right-angle H.FL plug (HFL-LP-DFS111-A).

ELECTRICAL SPECIFICATIONS ELECTRICAL SPECIFICATIONS

Differentiating Features and Key Specifications.

	3 V VERSION	5 V Version
Supply Power Magnetic Mount DC Levels Consumption	3.0 V ±0.3 V 20 mA max 15 mA typ	5.0 V +0.5 V or -0.75 V 30 mA max
Supply Power Unpackaged DC Levels Consumption	3.0 V ±0.3 V 5 mA to 13 mA max	N/A
Supply Power Bulkhead DC Levels Consumption	3.0 V ±0.5 V 35 mA max	5.0 V +0.25 or -0.75 V 35 mA max
Frequency Range	1,575.42 MHz ±1.023 MHz	
Gain Magnetic Mount & Unpackaged	27 dBi ±3dBi @ typical temperature ±4dBi @ operating temperature	
Bulkhead	28 dBi ±3dBi @ typical temperature ±4dBi @ operating temperature	
Output Impedance	50 Ω	
LNA Noise Figure Magnetic Mount & Unpackaged	27 dBi ±3dBi @ typical temperature ±4dBi @ operating temperature	
Bulkhead	1.8 dB max (25 °C) 2.3 dB max (85 °C)	3.3 dB max (25 °C) 3.8 dB max (85 °C)

Gain is for when antenna module is mounted on 60 mm x 60 mm ground plane.

Max is at operating temperature (-40 °C to +85 °C).

Typ is at typical temperature (25 °C ±5 °C).

ENVIRONMENTAL SPECIFICATIONS

Temperature

Typical 25 °C ±5 °C

Operating -40 °C to +85 °C

Storage -40 °C to +100 °C

Humidity 20% to 95%

Waterproofing Waterproof (JIS D0203 S2)

(Magnetic Mount & Bulkhead only)

Shock

Vertical axis 50 G

All axis 30 G

Vibration

10 Hz to 200 Hz Log sweep 3.0 g

(Sweep time: 15 minutes) 3 axis

Magnetic Mount Pulling Force

Pulling Force 29.4 N

Withstand Up to speed of 180 Km/h

Cable Pulling Force 49 N minimum (room temp)

ORDERING INFORMATION

MODEL TYPE	PART NUMBER	ORDER QUANTITY			
Magnetic Mount	66800-00	20	80	400	400 x n
	66800-40				
	66800-50				
	66800-52				
Unpackaged	66801-00	1	120	480	400 x n
Bulkhead	70228-70	1	96	480	400 x n
	70228-00				400 x n

NORTH AMERICA

Trimble Navigation Limited
Corporate Headquarters
935 Stewart Drive
Sunnyvale, CA 94085
+1-800-787-4225 Phone
+1-408-481-7741 Phone
Email: AD_Sales@trimble.com

EUROPE

Trimble Navigation Europe
+4670-544-10-20 Phone

KOREA

Trimble Export Ltd, Korea
+82-2-555-5361 Phone

CHINA

Trimble Navigation Ltd, China
+86-10-8857-7575 Phone

