

# EMBEDDED SMARC 2.1

## conga-SA7



- SMARC 2.1 module based on Intel® Atom® x6000E Series and Intel® Pentium® and Celeron® J and N Series processors
- High performance Intel® UHD Graphics (Gen11)
- Options for Industrial Temperature Range -40°C to 85°C
- Options for Time Sensitive Networking and Time Coordinated Computing for improved Realtime Capability
- Up to 4.267 MT/s Memory Support

<b>Form Factor</b>	SMARC Specification 2.1   82x50 mm					
<b>CPU</b>	Processor	TDP	Cores/Threads	Base Frequency/max. Turbo	Gfx Gen.11	Intel Use Condition
	J6413	10W	4 / 4	1.8 GHz / 3.0 GHz	16 EU	PC Client
	J6426	10W	4 / 4	2.0 GHz / 3.0 GHz	32 EU	PC Client
	x6211E	6W	2 / 2	1.3 GHz / 3.0 GHz	16 EU	Embedded
	x6413E	9W	4 / 4	1.5 GHz / 3.0 GHz	16 EU	Embedded
	x6425E	12W	4 / 4	2.0 GHz / 3.0 GHz	32 EU	Embedded
	x6212RE	6W	2 / 2	1.2 GHz / ---	16 EU	Industrial
	x6414RE	9W	4 / 4	1.5 GHz / ---	16 EU	Industrial
	x6425RE	12W	4 / 4	1.9 GHz / ---	32 EU	Industrial
<b>DRAM</b>	max. 16GB onboard LPDDR4x   up to 4.267 MT/s					
<b>Ethernet</b>	2x Intel® GbE with TSN support and Out-Of-Band Management   2x real-time trigger					
<b>I/O Interfaces</b>	2x USB 3.1 Gen2 (1x OTG)   6x USB 2.0 (1x OTG)   1x SATA III   1x SDIO   up to 4x PCIe Gen3   2x I <sup>2</sup> C Bus   1x SPI   1x eSPI   4x UART   GPIO   2x CAN   onboard M.2 1216 WiFi/BT module (optional)					
<b>Mass Storage</b>	eMMC 5.1 onboard flash up to 64GB (optional up to 128GB)					
<b>Audio</b>	Intel® HD Audio					
<b>Graphics</b>	Intel® UHD Graphics (Gen11)					
<b>LVDS</b>	Dual channel LVDS transmitter   support for flat panels with 2x24 bit data mapping up to a resolution of 1920x1200 @60Hz   shared with eDP or 1x MIPI-DSI x4 (option)					
<b>Digital Display Interface</b>	2x DDI up to 4096x2160p					
<b>congatec Board controller</b>	Multistage watchdog   non-volatile user data storage   manufacturing and board Information   board statistics   fast mode and multi-master I <sup>2</sup> C bus   power loss control					
<b>Embedded BIOS Feature</b>	AMI Aptio® UEFI firmware   32 Mbyte serial SPI with congatec Embedded BIOS feature   OEM Logo   OEM CMOS Defaults   LCD Control   Display Auto Detection   Backlight Control   Flash Update					
<b>Power Management</b>	ACPI 5.0 compliant   Smart Battery Management					
<b>Operating Systems</b>	Microsoft® Windows 10   Microsoft® Windows 10 IoT Enterprise   Linux   Android   Yocto   RTS Hypervisor					
<b>Power Consumption</b>	tbd.   see manual for full details					
<b>Temperature Range</b>	Commercial:	Operating Temperature: 0 to +60°C		Storage Temperature: -20 to +80°C		
	Industrial:	Operating Temperature: -40 to +85°C		Storage Temperature: -40 to +85°C		
<b>Humidity</b>	Operating:	10 to 90% r. H. non cond.				
	Storage:	5 to 95% r. H. non cond.				
<b>Size</b>	82 x 50 mm (approx. 3,23" x 1,97")					




Distributore Italia: Contradata Milano S.r.l.

Via Solferino 12 - 20900 Monza (MB) - Italy  
Tel: (+39) 039-230.14.92 Email: info@contradata.it

[www.contradata.it](http://www.contradata.it)



# conga-SA7 | Block Diagram



© 2021 congatec GmbH.  
All rights reserved.

All data is for information purposes only. Although all the information contained within this document is carefully checked, no guarantee of correctness is implied or expressed. Product names, logos, brands, and other trademarks featured or referred are the property of their respective trademark holders. These trademark holders are not affiliated with congatec AG. Product not yet released for Mass Production. Preliminary Revision 1.5 – June 15<sup>th</sup>, 2021

# conga-SA7 | Order Information

Article	PN	Description
conga-SA7/x6425E-16G eMMC64	050100	SMARC 2.1 module with Intel® Atom® x6425E quad core processor with 2.0GHz core frequency up to 3.0GHz, 1.5MB cache, 16GB 3200MT/s LPDDR4x onboard memory and 64GB eMMC 5.1 onboard flash.
conga-SA7/x6413E-8G eMMC32	050101	SMARC 2.1 module with Intel® Atom® x6413E quad core processor with 1.5GHz core frequency up to 3.0GHz, 1.5MB cache, 8GB 3.200MT/s LPDDR4x onboard memory and 32GB eMMC 5.1 onboard flash.
conga-SA7/x6211E-4G eMMC32	050102	SMARC 2.1 module with Intel® Atom® x6211E dual core processor with 1.3GHz core frequency up to 3.0GHz, 1.5MB cache, 4GB 3.200MT/s LPDDR4x onboard memory and 32GB eMMC 5.1 onboard flash.
conga-SA7/i-x6425RE-8G eMMC32	050110	SMARC 2.1 module with Intel® Atom® x6425RE quad core processor with 1.9GHz core frequency, 1.5MB cache, 8GB 4267MT/s LPDDR4x onboard memory and 32GB eMMC 5.1 onboard flash. Industrial grade temperature range from -40°C to 85°C.
conga-SA7/i-x6414RE-4G eMMC32	050111	SMARC 2.1 module with Intel® Atom® x6414RE quad core processor with 1.5GHz core frequency, 1.5MB cache, 4GB 3.200MT/s LPDDR4x onboard memory and 32GB eMMC 5.1 onboard flash. Industrial grade temperature range from -40°C to 85°C.
conga-SA7/i-x6212RE-4G eMMC32	050112	SMARC 2.1 module with Intel® Atom® x6212RE dual core processor with 1.2GHz core frequency, 1.5MB cache, 4GB 3.200MT/s LPDDR4x onboard memory and 32GB eMMC 5.1 onboard flash. Industrial grade temperature range from -40°C to 85°C.
conga-SA7/J6426-16G eMMC64	050120	SMARC 2.1 module with Intel® Pentium® J6426 quad core processor with 2.0GHz core frequency up to 3.0GHz, 1.5MB cache, 16GB 3200MT/s LPDDR4x onboard memory and 64GB eMMC 5.1 onboard flash.
conga-SA7/J6413-8G eMMC32	050121	SMARC 2.1 module with Intel® Celeron® J6413 quad core processor with 1.8GHz core frequency up to 3.0GHz, 1.5MB cache, 8GB 3.733MT/s LPDDR4x onboard memory and 32GB eMMC 5.1 onboard flash.
conga-SA7/i-CSP-B	050150	Passive cooling solution for SMARC 2.1 module conga-SA7 with lidded Intel Atom x6000E processors. All standoffs are with 2.7mm bore hole.
conga-SA7/i-HSP-B	050151	Standard heatspreader for SMARC 2.1 module conga-SA7 with lidded Intel Atom x6000E processors. All standoffs are with 2.7mm bore hole.
conga-SA7/HSP-B	050152	Standard heatspreader for SMARC 2.1 module conga-SA7 with open-die Intel Pentium and Celeron J and N processors. All standoffs are with 2.7mm bore hole.
conga-SA7/CSP-B	050153	Passive cooling solution for SMARC 2.1 module conga-SA7 with open-die Intel Pentium and Celeron J and N processors. All standoffs are with 2.7mm bore hole.



**Distributore Italia: Contradata Milano S.r.l.**

Via Solferino 12 - 20900 Monza (MB) - Italy  
Tel: (+39) 039-230.14.92 Email: info@contradata.it

© 2021 congatec GmbH.  
All rights reserved.

All data is for information purposes only. Although all the information contained within this document is carefully checked, no guarantee of correctness is implied or expressed. Product names, logos, brands, and other trademarks featured or referred are the property of their respective trademark holders. These trademark holders are not affiliated with congatec AG. Product not yet released for Mass Production.  
Preliminary Revision 1.5 – June 15<sup>th</sup>, 2021



[www.contradata.it](http://www.contradata.it)