

Datasheet

M.2 (S80) 3IE7 series

- SATA III solution for industrial field
- Exclusive L³ architecture
- DRAM-less, 100% data integrity
- Excellent random performance
- Supports TRIM/NCQ/SMART
- Built in iData Guard
- Compatible with M.2 2280-D2-B-M standard
- Designed with hardware LDPC ECC engine



Introduction

Innodisk M.2 (S80) 3IE7 is SATA III 6.0 Gb/s flash based disk, which adopts latest SATA III NAND controller with Innodisk's exclusive L³ FW architecture. The upgraded L³ FW architecture, combining Innodisk signature 4K mapping algorithm L² FW architecture with powerful LDPC technology, makes 3IE7 series have outstanding high IOPS, better data integrity and extended lifespan through reducing the bad block number happening. Built-in thermal sensor, and iData Guard ensure data integrity and reliability of 3IE7 for industrial applications.

Innodisk M.2 (S80) 3IE7 is designed for industrial field, and supports several standard features, including TRIM, NCQ, and S.M.A.R.T. In addition, Innodisk's exclusive industrial-oriented firmware provides a flexible customization service, making it perfect for a variety of industrial applications.


innodisk

Distributore Autorizzato per l'Italia:

Contradata Milano S.r.l.

Via Solferino 12, 20900 Monza (MB) - Italy

Tel: (+39) 039-230.14.92 | Email: info@contradata.it




www.contradata.it

M.2 (S80)

3IE7 series

Diagram



Specifications

Interface	SATA III
Flash Type	iSLC (3D TLC)
P/E cycle	30,000
Capacity	20GB~320GB
Max. Channels	4
Sequential R/W (MB/sec, max.)	550/490
Max. Power Consumption	1.98W(3.3V x600mA)
Thermal Sensor	√
External DRAM buffer	-
H/W Write Protect	Optional
ATA Security	√
S.M.A.R.T.	√
Dimension (WxLxH)	22.0 X 80.0 X 3.5 mm (Max)
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -55°C ~ +95°C MTBF: 3 million hours

© 2021 Innodisk Corporation.
All right reserved. Specifications are
subject to change without
prior notice.

20190425

Operation Temp.	20GB	40GB	80GB	160GB	320GB
Standard Grade (0°C ~ +70°C)	DHM28-20GDK1EC*DF	DHM28-40GDK1EC*QF	DHM28-80GDK1EC*QF	DHM28-A60DK1EC*QF	DHM28-D2GDK1ECAQF
Industrial Grade (-40°C ~ +85°C)	DHM28-20GDK1EW*DF	DHM28-40GDK1EW*QF	DHM28-80GDK1EW*QF	DHM28-A60DK1EW*QF	DHM28-D2GDK1EWAQF

*. PCB version control



Distributore Autorizzato per l'Italia:

Contradata Milano S.r.l.

Via Solferino 12, 20900 Monza (MB) - Italy

Tel: (+39) 039-230.14.92 | Email: info@contradata.it



www.contradata.it