


Datasheet

M.2 (S42) 3TG6-P series

- SATA III solution for industrial field
- Exclusive L³ architecture
- AES-256bits encryption
- Excellent random performance
- Supports TRIM/NCQ/SMART
- Built in iData Guard
- Compatible with M.2 2242-D2-B-M standard
- Designed with hardware LDPC ECC engine




Introduction

Innodisk M.2 (S42) 3TG6-P is SATA III 6.0 Gb/s flash based disk, which delivers excellent performance, especially in random data transfer rate, and which offers reliability making it the ideal solution for a variety of applications, including embedded system, industrial computing, and enterprise field. M.2 (S42) 3TG6-P not only performs unmatched performance, but also designed with Innodisk owned technical knowhow to ensure the data integrity and highest levels of reliability.

Innodisk M.2 (S42) 3TG6-P is designed for industrial field, and supports several standard features, including TRIM, NCQ, and S.M.A.R.T. In addition, Innodisk's exclusive industrial-oriented firmware provides a flexible customization service, making it perfect for a variety of industrial applications.

M.2 (S42) 3TG6-P series

Diagram



Specifications

Interface	SATA III
Flash Type	3D TLC
P/E cycle	3,000
Capacity	128GB~1TB
Max. Channels	4
Sequential R/W (MB/sec, max.)	510/410
Max. Power Consumption	2.8W (850mA x 3.3V)
Thermal Sensor	✓
External DRAM buffer	✓
H/W Write Protect	-
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	22.0 X 42.0 X 3.5 mm
Environment	Vibration: 20G @ 7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -40°C ~ + 85°C MTBF: 3 million hours

Ordering Information

Operation Temp.	128GB	256GB	512GB	1TB
Standard Grade (0°C ~ +70°C)	DGM24-A28M71GCBDL	DGM24-B56M71GCAQL	DGM24-C12M71GCAQL	DGM24-01TM71GCAQQ
Industrial Grade (-40°C ~ +85°C)	DGM24-A28M71GWBDL	DGM24-B56M71GWAQL	DGM24-C12M71GWAQL	DGM24-01TM71GWAQQ