


PCIe-9101/9121/9141

16/32 Channels, Multiplexer, High Performance
Multifunction Data Acquisition Card



Features

- PCI Express bus
- 32/16 single-ended or 16/8 differential analog input channels
- 16-bit high A/D resolution
- Onboard 4k-sample A/D FIFO
- Supports programmable voltage input range of $\pm 10V$, $\pm 5V$, $\pm 2.5V$, $\pm 1.25V$, $\pm 0.625V$, $\pm 0.3125V$
- Up to 1024 configuration programmable gain amplifiers
- 2-ch 16-bit multiplying analog outputs with waveform generation
- Onboard 1k-sample D/A FIFO
- 16-ch TTL digital input/16-ch TTL digital output
- Up to 2 independent full function general purpose timer counters
- Direct memory access channels offload CPU utilization
- Internal software and external digital/analog trigger support
- Fully automated calibration
- Board ID switch

Introduction

The PCIe-91xx series are PCI Express multi-function data acquisition cards for industrial applications. They feature a high sample rate, high resolution and high density I/O design which allows for easier integration of multiple functions in a single card useful in a variety of applications including data logging, process control, and condition monitoring.

Key benefits

- **Support Operating System**
Windows 7/10/11 x86/x64 or later, Linux
- **Driver and SDK**
LabVIEW, C/C++, Visual Basic, Visual Studio.NET
- **Software Utility**
ACE, Soft-Front Panel

Key benefits

- High density design with many input/output functions packed into each card.
- Programmable gain amplifiers for higher analog input accuracy.
- Direct memory access channels offload CPU utilization.
- Easy to use utility/SDK simplifies design effort.

Ordering Information

- **PCIe-9101**
16-ch 16-bit 250KS/s Multifunction DAQ
- **PCIe-9121**
16-ch 14-bit 800KS/s Multifunction DAQ
- **PCIe-9141**
16-ch 16-bit 1MS/s Multifunction DAQ

Terminal Boards & Cables

- **DIN-37D-01**
Terminal board with one 37-pin D-sub connector and DIN-rail mounting (Cables not included.)
- **ACL-10137-1MM**
37-pin D-sub male/male cable, 1 M
- **ACL-10120-1**
20-pin flat cable, 1 M

Specifications

Model Name	PCIe-9101	PCIe-9121	PCIe-9141
Analog Input			
Number of Channels	16 single-ended (SE) or 8 differential input (DI)		
Resolution	16-bit	14-bit	16-bit
Sampling Rate	Single-channel: 250kS/s Scanning: 100kS/s	Single-channel: 800 kS/s Scanning: up to 400 kS/s	Single-channel: 1MS/s Scanning: up to 500 kS/s
FIFO buffer size	Onboard 4k samples		
Input Range	$\pm 10\text{ V}$, $\pm 5\text{ V}$, $\pm 2.5\text{ V}$, $\pm 1.25\text{ V}$, $\pm 0.625\text{ V}$, $\pm 0.3125\text{ V}$		
Input impedance	10M Ω		
Input coupling	DC		
Overvoltage protection	Continuous $\pm 20\text{ V}$	Continuous $\pm 15\text{ V}$	
Trigger Source	Software Digital Analog		
Data Transfer	Polling DMA		
SNR	90 dB	84 dB	90 dB
ENOB	14.5 bit	13.5 bit	14.5 bit
Analog Output			
Number of Channels	2		
Resolution	16 Bit		
Output Range	$\pm 10\text{ V}$		
FIFO buffer size	Onboard 1K samples (2-channel share)		
Output driving capacity	$\pm 5\text{ mA max}$		
Slew rate	10 V/ μs		

Specifications

Model Name	PCIe-9101	PCIe-9121	PCIe-9141
Settling time (0.1% of Full scale)		5 us	
Output coupling		DC	
Output impedance		< 0.1 ohm	
Trigger Source		Software Digital	
Data transfers		Polling DMA	
Digital Input			
Number of Channels		16	
Compatibility		TTL	
Input Impedance		pull-low 100K ohm	
Input frequency range		0.01Hz to 1M Hz	
FIFO buffer size		Onboard 512 samples	
Isolation		No	
Trigger Source		Software Digital	
Data Transfer		Polling DMA	
Digital Output			
Number of Channels		16	
Compatibility		TTL	
Input Impedance		pull-low 100Kohm	
Input frequency range		0.01Hz to 1M Hz	
FIFO buffer size		Onboard 512 samples	
Isolation		No	
Trigger Source		Software Digital	
Data Transfer		Polling DMA	
General Purpose Timer Counter			
Number of Channels		2	
Resolution		32 Bit	
Compatibility		TTL	
Clock Source		Internal clock fixed to 33M Hz. External clock 0.01Hz to 8M Max Selected by software	
Output Frequency		By internal clock: 16.5MHz By external clock: 32MHz Max	
General Specification			
Bus Type		PCI Express 1.0	
Bus Width		x1 lane	

Specifications

Model Name	PCIe-9101	PCIe-9121	PCIe-9141
Dimension (L x W x H)	169.55 mm x 16.15 mm x 98.4 mm		
Connector	37-pin D-type connector		
Operating Temperature	0°C to 60°C		
Storage Temperature	-40 to 85 °C		
Power Consumption	Typical: 71.6 mA@3.3V 261.5 mA@12V Max: 257.8 mA@3.3V 556.24 mA@12V		Typical: 35 mA@3.3V 105 mA@12V Max: 186 mA@3.3V 557 mA@12V

All products and company names listed are trademarks or trade names of their respective companies. Updated Oct. 21, 2022. ©2022 ADLINK Technology, Inc. All Rights Reserved. All pricing and specifications are subject to change without further notice.