

# DPM-1156

15.6", Capacitive / Resistive Touch Screen , Industrial Touch Display



## Features

- 15.6" LCD Capacitive / Resistive Touch
- Compact Structure, Front Panel IP65
- All Metal Structure Design, Durable
- Support Panel and VESA Installation



## Specifications

Display	
Size	15.6-inch
Resolution	1920*1080
Viewing Angle	85/85/85/58
Color Support	16.2M
Brightness	450 cd/m <sup>2</sup>
Contrast Ratio	800:1
Response Time	3/0 (Typ.)(Tr/Td) ms
Backlight	LED
Backlight Life	50000h

  

Touch Screen	
Type	Projection Multi Touch Capacitive Touch Screen 5-wire Resistive Touch Screen
Control Interface	USB
Surface Hardness	≥6H & 3H
Transmittance	85% & 78%

  

I/O Connectors	
USB	1 x USB2.0
Display	1 x VGA 1 x DVI 1 x HDMI/DP
Others	1 x DC-IN (2-Pin Phoenix)

  

Power Specification	
Power Input	DC 12~24V
Power Adapter	AC-DC, 12V@5A, 60W
Power Consumption	16W(Typ.)

  

Environmental	
Operating Temperature	-10~50°C
Storage Temperature	-20~60°C
Relative Humidity	10%-90%,@ 40°C (non-condensing)
Vibration	5~500Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Certifications	CE, FCC

  

Mechanical	
Housing	Aluminum alloy panel, all-metal structure
Mounting Method	Panel-mount, VESA-mount
Dimension (W x L x H)	399.4x 249.4 x 46 mm
Weight	3.45Kg

  

Packing List	
	1 x DPM-1156
	1 x AC-DC Power Adapter
	1 x USB Control Cable
	1 x Cable Buckle
	1 x Certificate
	1 x Warranty Card
	8 X Panel Mounting Buckles

## Dimensions

